

EWLD~J-SS

Unit size	Sound pressure level at 1 m from the unit in semispheric free field (rif.2 x 10 ⁻⁵ Pa)									Power
	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	dB(A)	dB(A)
110	64.6	69.1	74.1	78.5	73.6	71.2	58.6	55.7	79.0	88.9
130	64.6	69.1	74.1	78.5	73.6	71.2	58.6	55.7	79.0	88.9
145	64.6	69.1	74.1	78.5	73.6	71.2	58.6	55.7	79.0	88.9
165	64.6	69.1	74.1	78.5	73.6	71.2	58.6	55.7	79.0	88.9
195	64.6	69.1	74.1	78.5	73.6	71.2	58.6	55.7	79.0	88.9
235	67.3	67.3	72.8	77.8	72.3	73.3	62.3	58.8	79.0	88.9
265	67.3	67.3	72.8	77.8	72.3	73.3	62.3	58.8	79.0	88.9
290	67.6	72.1	77.1	81.5	76.6	74.2	61.6	58.7	82.0	94.4
310	67.6	72.1	77.1	81.5	76.6	74.2	61.6	58.7	82.0	94.4
330	67.6	72.1	77.1	81.5	76.6	74.2	61.6	58.7	82.0	94.4
360	67.6	72.1	77.1	81.5	76.6	74.2	61.6	58.7	82.0	94.4
390	67.6	72.1	77.1	81.5	76.6	74.2	61.6	58.7	82.0	94.4
430	69.2	71.3	76.5	81.2	76.0	75.4	63.8	60.5	82.0	94.4
470	70.3	70.3	75.8	80.8	75.3	76.3	65.3	61.8	82.0	94.4
500	70.3	70.3	75.8	80.8	75.3	76.3	65.3	61.8	82.0	94.4
530	70.3	70.3	75.8	80.8	75.3	76.3	65.3	61.8	82.0	94.4

- NOTE
1.

The values are according to ISO 3744 and are referred to: evaporator 12/7°C, saturated discharge temperature 45°C, full load operation.
2.

The above sound pressure levels will decrease by 4dB(A) when a compressor sound enclosure (option) is installed.