

| Air temperature (°C DB - °C WB) | | 27 - 19 | | | | | | | | | | | | | | | |
|---|-------------------|------------------------|---------------------------|------------|---------------------|------------------------|---------------------------|------------|---------------------|------------------------|---------------------------|------------|---------------------|------------------------|---------------------------|------------|---------------------|
| Water temperature (Entering °C - leaving °C) | | 6 - 11 | | | | 7 - 12 | | | | 8 - 13 | | | | 9 - 14 | | | |
| Model | Air flow | Total cooling capacity | Sensible cooling capacity | Water flow | Water pressure drop | Total cooling capacity | Sensible cooling capacity | Water flow | Water pressure drop | Total cooling capacity | Sensible cooling capacity | Water flow | Water pressure drop | Total cooling capacity | Sensible cooling capacity | Water flow | Water pressure drop |
| | m ³ /h | W | W | l/h | kPa | W | W | l/h | kPa | W | W | l/h | kPa | W | W | l/h | kPa |
| FWP02AT | 300 | 2260 | 1560 | 388 | 6 | 2010 | 1460 | 345 | 5 | 1710 | 1340 | 293 | 4 | 1440 | 1230 | 247 | 3 |
| | 400 | 2920 | 2010 | 501 | 9 | 2610 | 1880 | 448 | 8 | 2250 | 1740 | 386 | 6 | 1840 | 1580 | 315 | 4 |
| | 500 | 3530 | 2430 | 605 | 13 | 3160 | 2270 | 542 | 11 | 2740 | 2110 | 470 | 8 | 2270 | 1930 | 390 | 6 |
| FWP03AT | 300 | 2660 | 1760 | 456 | 10 | 2420 | 1660 | 415 | 9 | 2150 | 1540 | 369 | 7 | 1840 | 1420 | 317 | 5 |
| | 400 | 3450 | 2290 | 591 | 16 | 3140 | 2160 | 539 | 14 | 2790 | 2010 | 479 | 11 | 2420 | 1860 | 416 | 8 |
| | 500 | 4190 | 2790 | 719 | 23 | 3820 | 2630 | 655 | 19 | 3400 | 2450 | 583 | 15 | 2950 | 2270 | 507 | 12 |
| FWP04AT | 300 | 2880 | 1880 | 494 | 8 | 2640 | 1770 | 453 | 7 | 2370 | 1650 | 407 | 6 | 2050 | 1520 | 353 | 4 |
| | 400 | 3790 | 2490 | 651 | 13 | 3490 | 2340 | 598 | 11 | 3130 | 2190 | 538 | 9 | 2750 | 2030 | 472 | 7 |
| | 500 | 4680 | 3070 | 802 | 18 | 4290 | 2890 | 737 | 16 | 3860 | 2700 | 663 | 13 | 3400 | 2510 | 584 | 10 |
| FWP05AT | 600 | 4460 | 3030 | 765 | 12 | 3990 | 2840 | 685 | 10 | 3480 | 2630 | 597 | 8 | 2890 | 2410 | 497 | 6 |
| | 800 | 5670 | 3840 | 972 | 18 | 5080 | 3600 | 873 | 15 | 4460 | 3350 | 765 | 12 | 3760 | 3090 | 646 | 9 |
| | 1000 | 6780 | 4580 | 1162 | 25 | 6080 | 4300 | 1044 | 21 | 5340 | 4010 | 918 | 16 | 4540 | 3700 | 779 | 12 |
| FWP06AT | 600 | 4680 | 3200 | 804 | 6 | 4120 | 2960 | 706 | 5 | 3420 | 2680 | 587 | 3 | 2970 | 2510 | 510 | 3 |
| | 800 | 6130 | 4150 | 1053 | 9 | 5450 | 3870 | 936 | 8 | 4690 | 3560 | 805 | 6 | 3750 | 3200 | 644 | 4 |
| | 1000 | 7470 | 5020 | 1282 | 13 | 6670 | 4680 | 1144 | 11 | 5780 | 4330 | 993 | 8 | 4770 | 3940 | 820 | 6 |
| FWP07AT | 600 | 5450 | 3590 | 935 | 11 | 4960 | 3370 | 852 | 9 | 4430 | 3140 | 760 | 7 | 3830 | 2890 | 657 | 6 |
| | 800 | 7100 | 4680 | 1218 | 17 | 6470 | 4400 | 1111 | 14 | 5800 | 4110 | 995 | 12 | 5060 | 3810 | 868 | 9 |
| | 1000 | 8660 | 5700 | 1486 | 24 | 7900 | 5370 | 1355 | 20 | 7080 | 5020 | 1215 | 17 | 6190 | 4660 | 1063 | 13 |

NOTES - HINWEISE - ΣΗΜΕΙΩΣΕΙΣ - NOTAS - REMARQUES - NOTE - OPMERKINGEN - ПРИМЕЧАНИЯ - NOTLAR

- Air temperature (°C DB - °C WB)
Lufttemperatur (°C DB - °C WB)
Θερμοκρασία αέρα (°C DB - °C WB)
Temperatura del aire (°C BS - °C BH)
Température de l'air (°C BS - °C BH)
Temperatura aria (°C BS - °C BU)
Luchttemperatuur (°CDB - °CNB)
Температура воздуха (°C сух.т. - °C вл.т.)
Hava sıcaklığı (°C DB - °C WB)
- Water temperature (Entering °C - leaving °C)
Wassertemperatur (Einlass °C - Auslass °C)
Θερμοκρασία νερού (εισόδου °C - αναχώρησης °C)
Temperatura del agua (entrada °C - salida °C)
Température de l'eau (°C en entrée - °C en sortie)
Temperatura acqua in uscita (Entrata °C - Uscita °C)
Watertemperatuur (Ingaand °C - uitgaand °C)
Температура воды (поступающая °C - на выходе °C)
Su sıcaklığı (Giriş °C - Çıkış °C)
- Model
Modell
Μοντέλο
Modelo
Modèle
Modello
Model
Модель
Model
- Air flow (m³/h)
Luftstrom (m³/h)
Ροή αέρα (m³/h)
Caudal de aire (m³/h)
Débit de l'air (m³/h)
Portata d'aria (m³/ora)
Luchtdebit (m³/u)
Расход воздуха (м³/час)
Hava akışı (m³/h)
- Total cooling capacity (W)
Gesamt-Kühlleistung (W)
Συνολική ψυκτική απόδοση (W)
Capacidad de refrigeración total (W)
Puissance frigorifique totale (W)
Capacità di raffrescamento totale (W)
Totaal koelvermogen (W)
Общая холодопроизводительность (Вт)
Toplam soğutma kapasitesi (W)
- Sensible cooling capacity (W)
Sensible Kühlleistung (W)
Απόδοση ευσθησίας ψύξης (W)
Capacidad de refrigeración sensible (W)
Puissance frigorifique sensible (W)
Capacità di raffrescamento sensibile (W)
Koelvermogen gevoelige modus (W)
Холодопроизводительность по ощутимому теплу (Вт)
Hissedilebilir soğutma kapasitesi (W)
- Water flow (l/h)
Wasserdurchfluss (l/h)
Παροχή νερού (l/h)
Caudal de agua (l/h)
Débit de l'eau (l/h)
Portata acqua (L/ora)
Waterdebit (l/u)
Расход воды (л/ч)
Su akışı (l/h)
- Water pressure drop (kPa)
Wasserdruckabfall (kPa)
Πτώση πίεσης νερού (kPa)
Caída de presión del agua (kPa)
Baisse de la pression de l'eau (kPa)
Perdita di carico dell'acqua (kPa)
Waterdrukverlies (kPa)
Уменьшение напора воды (кПа)
Sı basınıncı düşüşü (kPa)