

FWW-DAT
FWL-DAT
FWM-DAT

Air Temperature (°C DB - °C WB)		22 16															
Water Temperature (Entering °C - leaving °C)		6 - 11				7 - 12				8 - 13				9 - 14			
Model		Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop
		W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa
FW 01 T	Max	880	840	152	5	820	940	140	4	730	910	125	4	650	880	111	3
	Med	720	740	124	4	660	710	114	3	610	690	104	3	550	670	95	2
	Min	640	570	110	3	580	570	100	2	540	560	92	2	490	540	84	2
FW 15 T	Max	1020	910	174	6	920	1030	158	5	830	990	142	4	730	950	125	3
	Med	880	790	152	4	800	840	138	4	720	810	123	3	640	780	110	2
	Min	720	660	123	3	670	670	115	3	620	650	106	2	560	630	96	2
FW 02 T	Max	1200	1000	205	5	1030	1070	176	4	920	1030	158	3	830	1000	143	3
	Med	1040	880	178	4	840	800	145	3	820	850	141	3	750	820	129	2
	Min	870	720	150	3	750	670	128	2	690	680	119	2	640	660	109	2
FW 25 T	Max	1450	1340	249	7	1240	1340	212	5	1110	1290	190	4	970	1240	166	3
	Med	1190	1100	204	5	1020	1060	176	4	940	1030	161	3	860	1000	147	3
	Min	970	830	166	3	840	780	144	3	790	780	136	2	730	750	125	2
FW 03 T	Max	1730	1470	296	5	1480	1440	255	3	1370	1400	235	3	1260	1350	216	3
	Med	1450	1200	249	3	1260	1120	216	3	1180	1130	203	2	1080	1090	186	2
	Min	1240	960	213	3	1090	890	186	2	920	820	158	1	860	810	149	1
FW 35 T	Max	1960	2010	336	4	1750	1930	301	4	1550	1850	266	3	1420	1800	243	2
	Med	1490	1410	256	3	1400	1420	240	2	1290	1380	222	2	1180	1340	203	2
	Min	1320	1070	226	2	1140	1000	196	2	1070	1040	184	2	980	1010	169	1
FW 04 T	Max	2480	2170	425	5	2140	2210	368	4	1970	2140	339	3	1810	2080	310	3
	Med	1990	1740	341	3	1720	1630	295	2	1620	1600	279	2	1490	1550	256	2
	Min	1750	1360	300	3	1520	1270	261	2	1290	1170	221	1	1230	1190	212	1
FW 06 T	Max	2820	2570	484	6	2390	2460	410	4	2120	2350	363	3	1930	2280	331	3
	Med	2150	1990	369	4	1980	1950	340	3	1830	1890	314	3	1670	1830	287	2
	Min	1960	1650	336	3	1700	1550	292	2	1590	1540	272	2	1460	1480	250	2
FW 08 T	Max	3850	3380	661	5	3290	3260	565	4	3040	3160	522	3	2780	3060	478	3
	Med	3140	2680	539	3	2720	2510	467	3	2570	2510	441	2	2360	2420	405	2
	Min	2730	2130	469	3	2380	1990	409	2	2010	1840	346	1	1940	1870	333	1
FW 10 T	Max	4790	4200	822	8	4000	4270	687	6	3550	4100	610	5	3120	3930	536	4
	Med	3380	3120	579	4	3130	3210	538	4	2890	3120	496	3	2650	3020	455	3
	Min	2770	2270	474	3	2400	2120	412	2	2170	2100	373	2	1990	2030	342	2