

FWW-DAT
FWL-DAT
FWM-DAT

Air Temperature (°C DB - °C WB)		25 18															
Water Temperature (Entering °C - leaving °C)		6 - 11				7 - 12				8 - 13				9 - 14			
Model		Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop
		W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa
FW 01 T	Max	1480	1110	254	13	1260	1030	217	9	1020	940	175	6	920	1050	158	5
	Med	1190	900	205	9	1010	830	174	6	810	750	139	4	740	790	126	4
	Min	1000	740	172	6	850	670	145	5	680	610	117	3	620	630	107	3
FW 15 T	Max	1680	1210	287	14	1430	1110	245	10	1160	1010	200	7	1040	1150	178	6
	Med	1460	1060	251	11	1250	980	215	8	1020	890	174	6	900	930	155	4
	Min	1210	890	208	8	1040	810	178	6	840	740	144	4	740	740	128	3
FW 02 T	Max	1890	1320	325	11	1640	1220	281	9	1360	1110	233	6	1140	1180	196	5
	Med	1640	1160	282	9	1420	1070	244	7	1180	970	202	5	980	960	169	4
	Min	1310	930	225	6	1130	860	194	5	930	780	160	3	780	720	134	2
FW 25 T	Max	2330	1750	400	15	2010	1620	346	12	1660	1490	286	8	1390	1490	238	6
	Med	1960	1460	336	11	1690	1350	289	9	1380	1240	237	6	1160	1180	199	4
	Min	1540	1100	264	7	1320	1010	227	6	1060	910	182	4	920	870	157	3
FW 03 T	Max	2820	1970	484	11	2440	1820	419	8	2010	1640	345	6	1660	1590	284	4
	Med	2290	1590	393	7	1970	1460	338	6	1590	1310	273	4	1320	1200	226	3
	Min	1690	1180	290	4	1460	1080	251	3	1300	1020	224	3	1140	950	196	2
FW 35 T	Max	3370	2550	578	11	2870	2350	492	9	2290	2130	392	6	2010	2160	346	5
	Med	2520	1890	432	7	2100	1730	361	5	1630	1600	280	3	1500	1550	257	3
	Min	1880	1340	322	4	1560	1210	267	3	1380	1140	237	2	1200	1070	205	2
FW 04 T	Max	4170	2940	715	12	3590	2710	617	9	2940	2450	504	6	2440	2460	418	4
	Med	3140	2280	538	7	2670	2090	458	5	2080	1860	357	3	1880	1800	322	3
	Min	2390	1670	410	4	2060	1540	354	3	1830	1440	315	3	1600	1350	274	2
FW 06 T	Max	4600	3400	788	14	3970	3150	682	10	3280	2880	562	7	2690	2740	463	5
	Med	3720	2720	639	9	3200	2510	549	7	2580	2270	443	5	2160	2140	371	4
	Min	3040	2160	522	7	2580	1970	444	5	2050	1760	352	3	1780	1660	306	3
FW 08 T	Max	6470	4590	1109	11	5590	4230	960	9	4590	3830	788	6	3730	3620	640	4
	Med	5060	3580	868	7	4320	3270	741	6	3360	2890	578	4	2850	2690	489	3
	Min	3780	2640	649	4	3230	2410	554	3	2870	2270	492	3	2500	2120	429	2
FW 10 T	Max	7730	5560	1325	19	6690	5150	1148	15	5540	4700	951	10	4520	4760	776	7
	Med	6000	4320	1030	12	5150	3980	885	9	4160	3590	714	6	3460	3540	595	5
	Min	3920	2830	672	6	3270	2570	561	4	2900	2420	498	3	2520	2280	433	3