

FWW-DAT
FWL-DAT
FWM-DAT

Air Temperature (°C DB - °C WB)		27 19															
Water Temperature (Entering °C - leaving °C)		6 - 11				7 - 12				8 - 13				9 - 14			
Model		Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop	Total cooling cap	Sensible cooling cap	Water flow	Water pressure drop
		W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa	W	W	l/h	kPa
FW 01 T	Max	1750	1280	301	17	1540	1200	264	13	1310	1120	226	10	1090	1200	188	7
	Med	1410	1040	242	12	1240	970	213	9	1060	900	181	7	880	900	151	5
	Min	1180	850	203	9	1040	790	179	7	890	730	152	5	710	670	122	3
FW 15 T	Max	1980	1390	339	18	1740	1300	298	14	1490	1210	256	11	1210	1110	209	8
	Med	1720	1220	296	14	1520	1140	261	11	1300	1060	223	9	1060	970	182	6
	Min	1430	1020	245	10	1260	950	216	8	1080	880	185	6	880	800	151	4
FW 02 T	Max	2210	1510	379	15	1960	1420	337	12	1700	1320	292	9	1410	1210	242	7
	Med	1910	1330	328	12	1700	1240	292	9	1480	1150	253	7	1230	1060	211	5
	Min	1530	1070	263	8	1360	1000	234	6	1180	930	202	5	970	850	167	3
FW 25 T	Max	2720	2000	467	20	2420	1880	415	16	2100	1760	360	13	1740	1620	299	9
	Med	2290	1670	392	15	2030	1570	348	12	1760	1460	301	9	1450	1350	249	7
	Min	1800	1260	309	10	1600	1180	275	8	1380	1090	237	6	1120	990	193	4
FW 03 T	Max	3290	2260	564	14	2930	2110	503	11	2540	1950	436	9	2110	1790	362	6
	Med	2670	1820	459	10	2380	1700	408	8	2060	1570	353	6	1680	1420	289	4
	Min	1990	1360	341	6	1760	1260	302	5	1500	1150	258	4	1320	1080	227	3
FW 35 T	Max	3980	2930	682	15	3510	2750	602	12	3000	2560	515	9	2410	2490	414	6
	Med	3000	2190	514	9	2630	2040	451	7	2220	1880	381	5	1800	1790	309	4
	Min	2280	1570	391	6	1980	1450	340	4	1610	1310	277	3	1400	1230	240	2
FW 04 T	Max	4870	3370	835	15	4330	3150	743	12	3750	2920	643	10	3090	2670	530	7
	Med	3690	2620	632	9	3270	2450	561	8	2800	2260	481	6	2230	2050	383	4
	Min	2850	1950	489	6	2510	1800	431	5	2100	1640	361	3	1860	1540	319	3
FW 06 T	Max	5360	3890	919	18	4770	3650	818	14	4140	3400	710	11	3430	3140	589	8
	Med	4350	3120	747	12	3870	2920	664	10	3340	2710	574	8	2730	2480	469	5
	Min	3570	2490	613	9	3170	2320	544	7	2710	2140	466	5	2150	1920	370	4
FW 08 T	Max	7520	5250	1289	15	6710	4910	1152	12	5830	4560	1001	9	4830	4170	829	7
	Med	5930	4110	1016	10	5270	3830	904	8	4530	3530	778	6	3630	3190	624	4
	Min	4510	3070	774	6	3970	2840	681	5	3310	2570	569	4	2910	2420	500	3
FW 10 T	Max	9000	6350	1544	25	8020	5960	1376	20	6960	5560	1196	16	5800	5120	995	11
	Med	7020	4950	1204	16	6240	4630	1071	13	5390	4300	924	10	4400	3930	756	7
	Min	4690	3290	804	8	4110	3050	706	6	3430	2780	588	5	2940	2600	505	3