

FWE-DATN5V3N-(L-R-S-T)

CALEFACCIÓN 2 TUBOS @ 0 ESP													
Temperatura del aire		BS: 20°C						BS: 22°C					
Temperatura del agua (Entrada °C - Salida °C)		ΔT=5						ΔT=5					
		50-45			45-40			50-45			45-40		
Modelo / Velocidad del ventilador		Ph	Wf	Dp	Ph	Wf	Dp	Ph	Wf	Dp	Ph	Wf	Dp
		kW	l/h	kPa	kW	l/h	kPa	kW	l/h	kPa	kW	l/h	kPa
FWE03DAT N5V3-L/R/S/T	1 (L)	1,66	285	12,90	1,34	230	8,50	1,54	264	11,10	1,21	209	7,00
	2	1,87	322	16,40	1,51	260	10,80	1,73	298	14,10	1,37	236	8,90
	3 (M)	2,09	360	20,30	1,69	290	13,40	1,93	333	17,50	1,53	263	11,00
	4	2,28	391	24,00	1,84	316	15,80	2,11	362	20,60	1,67	286	13,00
	5 (H)	2,47	426	28,30	2,00	344	18,60	2,29	394	24,30	1,81	312	15,40
FWE04DAT N5V3-L/R/S/T	1	1,98	341	10,40	1,60	275	6,70	1,83	315	8,90	1,46	250	5,50
	2 (L)	2,20	379	12,90	1,78	306	8,30	2,04	350	11,00	1,61	277	6,80
	3 (M)	2,47	424	16,20	1,99	343	10,50	2,28	393	13,80	1,81	311	8,60
	4	2,73	470	19,90	2,21	379	12,90	2,53	435	17,00	2,00	344	10,60
	5 (H)	2,95	507	23,20	2,38	409	15,10	2,73	469	19,80	2,16	371	12,40
FWE05DAT N5V3-L/R/S/T	1	2,08	358	11,50	1,68	289	7,40	1,92	331	9,80	1,52	262	6,10
	2 (L)	2,45	422	16,00	1,98	341	10,40	2,27	391	13,70	1,80	309	8,50
	3 (M)	2,88	495	22,10	2,32	400	14,30	2,66	458	18,90	2,11	362	11,80
	4	3,36	578	30,20	2,71	467	19,60	3,11	535	25,80	2,46	423	16,10
	5 (H)	3,58	615	34,20	2,89	496	22,20	3,31	569	29,30	2,62	450	18,20
FWE06DAT N5V3-L/R/S/T	1	2,63	453	7,40	2,12	366	4,90	2,44	419	6,40	1,93	332	4,00
	2	3,05	525	9,90	2,46	424	6,50	2,82	486	8,50	2,23	384	5,40
	3 (L)	3,64	626	14,10	2,94	505	9,20	3,37	579	12,10	2,66	458	7,60
	4 (M)	4,16	715	18,30	3,36	577	12,00	3,85	662	15,70	3,04	523	9,90
	5	4,58	788	22,20	3,70	636	14,50	4,24	729	19,00	3,36	577	12,00
	6 (H)	4,96	853	26,00	4,00	689	17,00	4,59	789	22,30	3,63	624	14,00
FWE07DAT N5V3-L/R/S/T	1	3,39	584	22,90	2,74	471	15,30	3,14	540	19,70	2,48	427	12,70
	2 (L)	3,91	672	29,90	3,15	542	19,90	3,62	622	25,80	2,86	492	16,60
	3	4,15	714	33,60	3,35	577	22,40	3,84	661	29,00	3,04	523	18,60
	4 (M)	4,45	766	38,40	3,60	618	25,50	4,12	709	33,10	3,26	561	21,20
	5	5,07	871	49,10	4,09	703	32,60	4,69	806	42,30	3,71	638	27,10
	6 (H)	5,40	930	55,70	4,36	751	26,90	5,00	860	48,00	3,96	681	30,60
FWE08DAT N5V3-L/R/S/T	1	3,96	681	21,80	3,20	550	15,10	3,67	630	19,10	2,90	499	12,90
	2 (L)	4,42	759	26,30	3,56	613	18,10	4,09	703	21,00	3,23	556	15,40
	3	4,63	797	28,70	3,74	643	19,80	4,29	737	25,00	3,39	583	16,70
	4	4,90	843	31,60	3,95	680	21,80	4,53	780	27,60	3,59	617	18,40
	5 (M)	5,44	936	38,10	4,39	755	26,10	5,04	866	33,20	3,98	685	22,00
	6 (H)	5,74	988	42,00	4,64	797	28,70	5,32	914	36,50	4,21	723	24,20
FWE10DAT N5V3-L/R/S/T	1	4,17	718	23,90	3,37	579	16,50	3,86	664	20,90	3,06	526	14,00
	2 (L)	4,82	829	30,70	3,89	669	21,10	4,46	767	26,80	3,53	607	17,90
	3	5,33	916	36,70	4,30	739	25,10	4,93	847	31,90	3,90	670	21,20
	4 (M)	6,14	1056	47,30	4,96	852	32,30	5,69	977	41,20	4,50	773	27,20
	5	6,88	1183	58,10	5,55	955	39,50	6,37	1094	50,50	5,04	866	33,20
	6 (H)	7,41	1275	66,60	5,98	1029	45,10	6,86	1179	57,80	5,43	933	37,90
FWE11DAT N5V3-L/R/S/T	1	4,46	768	26,80	3,60	620	18,50	4,13	710	23,40	3,27	562	15,70
	2 (L)	5,17	889	34,80	4,17	717	23,90	4,78	822	30,30	3,78	651	20,20
	3	5,64	969	40,60	4,55	782	27,80	5,22	897	35,30	4,13	710	23,40
	4 (M)	6,40	1101	51,00	5,17	888	24,70	5,92	1018	44,30	4,69	806	29,20
	5	7,28	1252	64,50	5,88	1011	43,70	6,74	1159	56,00	5,33	917	36,70
	6 (H)	7,87	1353	74,30	6,36	1092	50,30	7,28	1252	64,50	5,76	991	42,20

SÍMBOLOS

- Ph = Capacidad de calefacción total
- Wf = Caudal de agua
- Dp = Caída de presión del agua