

Notes

- 1) The total capacity of each connected indoor unit is up to ·11.0·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0· kW class
Wall-mounted ·CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXA-CW, CTXA-CB, CTXA-CS, CTXA-DG, CTXA-DP, CTXA-DL, CTXA-DC, CTXA-DY, CTXM-R, CTXM-A, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXA-CW, FTXA-CB, FTXA-CS, FTXA-DG, FTXA-DP, FTXA-DL, FTXA-DC, FTXA-DY, FTXM-R, FTXM-A, FTXJ-AB, FTXJ-AS, FTXJ-AW, FTXJ-AB9, FTXJ-AS9, FTXJ-AW9· series
- 3) Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB
- 4) ·CHVX· model is equivalent to room capacity of ·7.0· kW.
When ·CHVX· model is included in system installation:
 - a) Total connected capacity can be higher than the capacity mentioned in note ·1)·.
 - b) System design capacity shall NOT exceed the capacity mentioned in note ·1)·, once the ·CHVX· model is designed for simultaneous operation together with indoor air units.