

Notes

- 1) The total capacity of each connected indoor unit is up to ·11.0·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0· kW class
Wall-mounted ·CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXA-CW, CTXA-CB, CTXA-CS, CTXA-DG, CTXA-DP, CTXA-DL, CTXA-DC, CTXA-DY, CTXM-R, CTXM-A, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXA-CW, FTXA-CB, FTXA-CS, FTXA-DG, FTXA-DP, FTXA-DL, FTXA-DC, FTXA-DY, FTXM-R, FTXM-A, FTXJ-AB, FTXJ-AS, FTXJ-AW, FTXJ-AB9, FTXJ-AS9, FTXJ-AW9· series
- 3) Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- 4) Combination with CHVX model:
CHVX model is equivalent to a 7.0 kW unit related to the combination table for system design.
Once the product is designed for simultaneous operation, the overall connected capacity can be higher than the capacity mentioned in note 1) when the CHVX model is included.
However, system-designed capacity shall not exceed the capacity mentioned in the same paragraph.