

* Electrical meter specification

- Pulse meter type/voltage-free contact for 5 V DC detection by PCB.
- Possible number of pulses
 - 0.1 pulse/kWh
 - 1 pulse/kWh
 - 10 pulse/kWh
 - 100 pulse/kWh
 - 1000 pulse/kWh
- Pulse duration
 - minimum On time: 40ms
 - Minimum OFF time: 100ms
- Measurement type (depending on installation)
 - Single-phase AC meter
 - Three-phase AC meter
 - Balanced loads
 - Unbalanced loads

* Electrical meter installation guideline

- It is the responsibility of the installer to cover the complete power consumption with electrical meters (combination of estimation and metering is not allowed).
- Required number of electrical meters

Outdoor unit type		*(B/D)LQ(05/07)*			
Indoor unit type		Optional	*KMBUHCA(3V3/9W1)		
	Backup heater type		3V / 9W	9W	
	Backup heater power supply		1~ 230V	3~ 400V	
	Backup heater configuration		3 / 6 3 / 6 kW	6 / 9 6 / 9 kW	
Normal kWh rate power supply					
Electrical meter type	1~	1	1	1	-
	3~ balanced	-	-	1	-
	3~ unbalanced	-	-	-	1
Preferential kWh rate power supply					
Electrical meter type	1~	2	2	1	
	3~ balanced	-	-	-	
	3~ unbalanced	-	-	1	