

FWXV15-20A

Heating capacity tables

Air temperature (°C)		20°C														
Water temperature (Entering °C - leaving °C)		35°C-30°C			45°C-40°C			50°C-45°C			55°C-45°C			60°C-50°C		
Model	Fan	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop
		kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa
FWXV15AVEB	H	1.12	3.2	7	2.00	5.7	22	2.43	7.0	32	2.85	4.1	12	3.27	4.7	15
	M	0.83	2.4	4	1.50	4.3	13	1.82	5.2	19	2.13	3.1	7	2.44	3.5	9
	L	0.50	1.4	2	1.00	2.9	6	1.35	3.9	10	1.43	2.0	3	1.64	2.4	4
FWXV20AVEB	H	1.65	4.7	15	3.00	8.6	49	3.67	10.5	71	4.33	6.2	26	4.99	7.2	34
	M	1.12	3.2	7	2.00	5.7	22	2.43	7.0	32	2.86	4.1	12	3.29	4.7	15
	L	0.83	2.4	4	1.50	4.3	13	1.82	5.2	19	2.13	3.1	7	2.44	3.5	9

Air temperature (°CDB-°CWB)		22°CDB														
Water temperature (Entering °C - leaving °C)		35°C-30°C			45°C-40°C			50°C-45°C			55°C-45°C			60°C-50°C		
Model	Fan	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop	Heating capacity	Water flow	Water pressure drop
		kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa	kW	L/min	kPa
FWXV15AVEB	H	1.01	2.9	6	1.84	5.3	19	2.27	6.5	28	2.69	3.9	10	3.11	4.5	14
	M	0.75	2.2	3	1.38	4.0	11	1.70	4.9	16	2.01	2.9	6	2.31	3.3	8
	L	0.45	1.3	1	0.92	2.6	5	1.26	3.6	9	1.35	1.9	3	1.55	2.2	4
FWXV20AVEB	H	1.48	4.2	13	2.76	7.9	41	3.42	9.8	62	4.08	5.8	23	4.74	6.8	31
	M	1.00	2.9	6	1.84	5.3	19	2.27	6.5	28	2.70	3.9	10	3.12	4.5	14
	L	0.75	2.2	3	1.38	4.0	11	1.70	4.9	16	2.01	2.9	6	2.31	3.3	8