

Maximum cooling capacity

	T _{amb} [°C]	20		25		30		35		40		43	
	LWE [°C]	CC [kW]	PI [kW]	CC [kW]	PI [kW]	CC [kW]	PI [kW]	CC [kW]	PI [kW]	CC [kW]	PI [kW]	CC [kW]	PI [kW]
EPGA11DAV3*	7	11,78	2,53	12,01	2,97	11,40	3,45	10,80	3,93	9,33	3,94	8,44	3,94
	10	12,70	2,35	13,18	2,96	12,18	3,32	11,18	3,67	9,36	3,58	8,28	3,53
	13	13,63	2,18	14,36	2,96	12,96	3,18	11,56	3,40	9,40	3,23	8,11	3,13
	15	14,52	2,15	15,24	2,86	13,75	3,13	12,25	3,39	10,17	3,30	8,93	3,24
	18	15,86	2,11	16,57	2,72	14,93	3,05	13,29	3,37	11,33	3,39	10,15	3,40
	22	17,64	2,06	18,34	2,53	16,51	2,94	14,67	3,35	12,87	3,52	11,79	3,63
EPGA14DAV3*	7	13,23	3,10	13,51	3,61	12,83	3,99	12,15	4,37	10,49	4,40	9,50	4,42
	10	14,27	2,86	14,83	3,63	13,70	3,91	12,58	4,19	10,53	4,05	9,31	3,97
	13	15,30	2,63	16,15	3,66	14,58	3,83	13,00	4,01	10,58	3,70	9,12	3,51
	15	16,31	2,65	17,15	3,64	15,46	3,82	13,78	4,01	11,44	3,77	10,04	3,64
	18	17,83	2,69	18,64	3,63	16,79	3,81	14,95	4,00	12,74	3,89	11,42	3,82
	22	19,85	2,74	20,63	3,61	18,57	3,80	16,51	3,99	14,48	4,04	13,26	4,07
EPGA16DAV3*	7	14,75	3,72	15,01	4,26	14,25	4,58	13,50	4,90	11,66	4,91	10,55	4,91
	10	15,90	3,41	16,48	4,32	15,23	4,54	13,97	4,77	11,70	4,54	10,34	4,40
	13	17,05	3,11	17,95	4,37	16,20	4,50	14,45	4,63	11,75	4,17	10,14	3,89
	15	18,16	3,19	19,05	4,45	17,18	4,55	15,31	4,64	12,72	4,26	11,16	4,03
	18	19,83	3,30	20,71	4,57	18,66	4,61	16,61	4,66	14,16	4,40	12,69	4,24
	22	22,05	3,46	22,92	4,73	20,63	4,70	18,34	4,68	16,09	4,58	14,73	4,52

Symbols

CC	Cooling capacity at maximum operating frequency, measured according to EN 14511.
HC	Heating capacity at maximum operating frequency, measured according to EN 14511
PI	Power input is the total input of indoor and outdoor units, including the circulation pump; according to EN 14511.
LWE	Leaving water evaporator temperature [°C]
LWC	Leaving water condensor temperature [°C]
Tamb	Ambient temperature [°C DB]

Conditions

Cooling capacity

Capacity according to standard EN 14511 and valid for chilled water range $\Delta T = 3\sim 8^{\circ}\text{C}$.

Capacity values may not be extrapolated below 7°C leaving water temperature.

Heating capacity

Capacity according to standard EN 14511 and valid for heated water range $\Delta T = 3\sim 8^{\circ}\text{C}$.

Power input

Power input is the total input of indoor and outdoor units, including the circulation pump; according to EN 14511.

Notes

The capacity and the power input are valid for V3 models at 230 V.

The capacity and the power input are at maximum operation.