

Factory-mounted equipment for ·EAB(H/X)16DF*7·

Description	EAB(H/X)16DF*7	
Heating only model -EAB*7-	6V (8)	9W (8)
Reversible model -EABX*7-	6V (8)	9W (8)
Backup heater -2-4-6kW 1N~230 V-	o	-
Backup heater -2-4-6kW 3~230 V-	o	-
Backup heater -3-6-9kW 3N~400 V-	-	o

Outdoor combination table for ·*HB(H/X)(04/08)DF*7·

	Description	EPGA11DAV37	EPGA14DAV37	EPGA16DAV37
EABH16DF*7	Heating only	o	o	o
EABX16DF*7	Reversible	o	o	o

Kit availability for indoor units

Reference	Description	EAB*16DF*7	
EABH*7	Heating only indoor unit	6V	9W
EABX*7	Reversible indoor unit	6V	9W
EKRPI1HBA	Digital I/O PCB	(1)(2)	o
EKRPI1AHTA	Demand PCB	(3)	o
BRC1HHDA	Simplified user interface	o	o
EKPCCAB4	PC cable	(4)	o
EKHW5150D3V3	Domestic hot water tank -150 l 1~230 V-	o	o
EKHW5180D3V3	Domestic hot water tank -180 l 1~230 V-	o	o
EKHW5200D3V3	Domestic hot water tank -200 l 1~230 V-	o	o
EKHW5250D3V3	Domestic hot water tank -250 l 1~230 V-	o	o
EKHW5300D3V3	Domestic hot water tank -300 l 1~230 V-	o	o
EKHW5150P3V3	Domestic hot water tank -150 l 1~230 V-	o	o
EKHW5180P3V3	Domestic hot water tank -180 l 1~230 V-	o	o
EKHW5200P3V3	Domestic hot water tank -200 l 1~230 V-	o	o
EKHW5250P3V3	Domestic hot water tank -250 l 1~230 V-	o	o
EKHW5300P3V3	Domestic hot water tank -300 l 1~230 V-	o	o
EKHW5150D3V3	Domestic hot water tank -150 l 1~230 V-	o	o
EKHW5180D3V3	Domestic hot water tank -180 l 1~230 V-	o	o
EKHW5200D3V3	Domestic hot water tank -200 l 1~230 V-	o	o
EKHW5250D3V3	Domestic hot water tank -250 l 1~230 V-	o	o
EKHW5300D3V3	Domestic hot water tank -300 l 1~230 V-	o	o
EKHW5300PB	Domestic hot water tank with solar connection	(9)	o
EKHW5300PB	Domestic hot water tank with solar connection	(9)	o
EKHW5500PB	Domestic hot water tank with solar connection	(9)	o
EKHW5500PB	Domestic hot water tank with solar connection	(9)	o
EKHY3PART	Third-party tank connection kit for thermistor pocket	o	o
EKHY3PART2	Third-party tank connection kit for thermostat contact	o	o
BZKA7V3	Bizone kit	o	o
KRCS01-1	Remote indoor sensor	(5)	o
EKRSCA1	Remote sensor for outdoor	(5)	o
BRP069A61	LAN adapter for smartphone control	o	o
BRP069A62	LAN adapter for smartphone control	o	o
EKCC8-W	Universal centralised user interface	o	o
EKHBCONV	Conversion kit: heating only to reversible.	o	o
FWXV15AVEB	Heat pump convector	(6)	o
FWXV20AVEB	Heat pump convector	(6)	o
EVKHPC	Heat pump convector valve kit	o	o
EKRTWA	Wired room thermostat	o	o
EKTR1	Wireless room thermostat	o	o
EKRTETS	External sensor room thermostat	(7)	o

Kit availability for domestic hot water tanks

Reference	Description	FKHWP			
KHW	Domestic hot water tank with solar connection	300B	300PB	500B	500PB
*KSRPS4A	Solar kit	o	o	o	o

Kit availability for ·EKHWP·

Reference	Description	EABH16DF*7		EABX16DF*7	
		EKHW	P08/P	500B/PB	100B/P
EKEPRHLT3HX	Connection kit	o	o	o	o
EKEPRHLT5H	Connection kit	-	o	-	-
EKEPRHLT5X	Connection kit	-	-	-	o

Notes

- (1) PCB that provides additional output connections: · ·
 - (a) Control external heat source (bivalent operation).
 - (b) Output remote ON/OFF signal space heating/cooling
 - (c) Remote alarm output
- (2) Additional relays to allow bivalent control in combination with an external room thermostat are field-supplied.
- (3) PCB to receive up to 4 digital inputs for power limitation
- (4) Data cable for connection with PC.
- (5) Only 1 remote sensor can be connected: indoor OR outdoor sensor.
- (6) The valve kit is mandatory if a heat pump convector is installed on a reversible model (not mandatory for heating only models).
- (7) ·EKRTETS· can only be used in combination with ·*KTR1·.
- (8) The backup heater capacity depends on a user interface setting.
- (9) Dedicated connection kit available.

Remark

Other combinations than mentioned in this combination table are prohibited.

Kit availability for outdoor units

	EPGA11DAV37	EPGA14DAV37	EPGA16DAV37
EKBPH140L7	Bottom plate heater	o	o