

Factory-mounted equipment for -ETS(H/X)12P*EF*

Description	ETS(H/X)*12P30EF	ETS(H/X)*12P50EF
Domestic hot water tank -300l integrated-	o	-
Domestic hot water tank -500l integrated-	-	o

Outdoor combination table for -ETS(H/X)12P*EF*

		EPRA08EA(V3/W1)	EPRA10EA(V3/W1)	EPRA12EA(V3/W1)
ETSH*12P(30/50)EF	Heating only indoor unit	o	o	o
ETSX*12P(30/50)EF	Reversible indoor unit	o	o	o

Kit availability for indoor units

Reference	Description	ETS(H/X)12P*EF	ETS(H/X)B12P*EF
EKRP1HBAA	Digital I/O PCB	*(1) (2) o	o
EKRP1AHTA	Demand PCB	*(3) o	o
BRC1HHDA*	HCI (Human Comfort Interface)	o	o
EKPCCAB4	PC cable	*(4) o	o
KRCS01-1	Remote indoor sensor	*(5) o	o
EKRSCA1	Remote sensor for outdoor	*(5) o	o
EKCC8-W	Universal centralised user interface	o	o
DCOM-LT/IO	DCOM gateway	-	-
DCOM-LT/MB	DCOM gateway	-	-
EKCC8-W	Cascade control	o	o
EKHVCONV4	Conversion kit: heating only to reversible.	-	-
FWXV10-15-20ATV3	Heat pump convector	*(6) o	o
FWXT10-15-20ATV3	Heat pump convector	*(6) o	o
FWXM10-15-20ATV3	Heat pump convector	*(6) o	o
EKVKHPC	Heat pump convector valve kit	-	-
EKRTRWA	Wired room thermostat	o	o
EKRTR1	Wireless room thermostat	o	o
EKRTE5	External sensor room thermostat	*(7) o	o
EKWUFHTA1V3	Multi-zoning base unit 230 V	*(9) -	-
EKWCTRD1V3	Digital thermostat 230 V	*(9) -	-
EKWCTRAN1V3	Analogue thermostat 230 V	*(9) -	-
EKWCVATR1V3	Actuator 230 V	*(9) -	-
EKRELSG	Relay for Smart Grid	o	o
BRP069A71	WLAN module	*(10) o	o
EKUHWG3D	-G3- kit	*(11) -	-
AFVALVE1	Freeze protection valve	o	o
ESAE04A01*	Daikin Residential Controller	-	-
EKECBUAF3V	Inline backup heater 3kW	o	o
EKECBUAF6V	Inline backup heater 6kW	o	o
EKECBUAF9W	Inline backup heater 9kW	o	o
EKECBUCO1AF	Inline BUH connection kit topgrade	o	o
156021	dirt seperator	o	o
EKECBIVCOAF	Biv Connector Kit	-	o
EKECDBC0AF	DB connector Kit	o	o

Kit availability for outdoor units

Reference	Description	EPRA08EA(V3/W1)	EPRA10EA(V3/W1)	EPRA12EA(V3/W1)
EKMST1	Mounting stand	o	o	o
EKMST2	Mounting stand	o	o	o

Reference	Description	ETS(H/X)*12P*EF
EKMIKPOAF	Mixing kit – PCB only	o
EKMIKPHAF	Mixing kit – PCB with hydraulics	o
EKMIKHMAF	Hydraulics – mixed pump group	*(12) o
EKMIKHUAF	Hydraulics – unmixed pump group	*(12) o
EKMIKBVAF	Balancing vessel	o
EKMIKDIAF	Distributor for balancing vessel	*(13) o

Notes

- (1) PCB that provides additional output connections:
 - (a) Control external heat source (bivalent operation).
 - (b) Output remote ON/OFF signal space heating/cooling
 - (c) Remote alarm output
- (2) Additional relays to allow bivalent control in combination with an external room thermostat are field-supplied.
- (3) PCB to receive up to -4- digital inputs for power limitation
- (4) Data cable for connection with PC.
- (5) Only 1 remote sensor can be connected: indoor OR outdoor sensor.
- (6) The valve kit is mandatory if a heat pump convector is installed on a reversible model (not mandatory for heating only models).
- (7) -EKRTETS- can only be used in combination with -EKRTR1-
- (8) The backup heater capacity depends on a user interface setting.
- (9) Multi-zoning wired controls
- (10) The WLAN cartridge is supplied in the accessory bag of the unit and is meant to be plugged into the SD card slot on the MMI-2. In case of bad signal reception, the WLAN cartridge can be removed and replaced by the WLAN module.
- (11) This kit is mandatory for the UK models.
- (12) Only possible in combination with -EKMIKPOAF-
- (13) Only possible in combination with -EKMIKBVAF- and -EKMIKPHAF- or -EKMIKHUAF-
- (14) Only possible in combination with -HBKIT*-
- (15) Only possible in combination with -ETVZ*-

Remark

Other combinations than mentioned in this combination table are prohibited.