

LMSEY1A09AVM0*

LMSEY1A13AVM0*

Max cooling capacity

Model name	Rated operating requecy [Hz]	External temperature [°CDB]	Cooling capacity							
			Cold room temperature [°C]							
			-25	-20	-15	-10	-5	0	5	10
LMSEY1A09AVM0*	50 Hz	45	353	439	544	598	717	832	942	1045
		40	395	485	588	688	787	879	984	1061
		35	437	530	631	730	828	918	1024	1111
		32	463	560	658	755	853	950	1048	1145
		30	471	570	669	768	866	966	1066	1177
		25	504	608	715	819	919	1028	1140	1257
		20	538	646	761	870	972	1090	1214	1336
		15	572	684	807	921	1031	1152	1288	1416
		10	605	722	853	972	1089	1215	1362	1496
		5	639	760	899	1023	1154	1277	1436	1575
LMSEY1A13AVM0*	50 Hz	45	462	588	733	598	717	832	942	1045
		40	516	649	792	931	1062	1184	1311	1061
		35	571	710	850	988	1117	1237	1364	1484
		32	604	750	886	1023	1151	1280	1396	1530
		30	615	763	901	1040	1168	1301	1420	1573
		25	659	814	963	1109	1240	1385	1519	1679
		20	703	865	1025	1178	1312	1469	1617	1786
		15	746	915	1087	1247	1391	1553	1716	1892
		10	790	966	1149	1317	1470	1636	1814	1998
		5	834	1017	1211	1386	1558	1720	1913	2105

Min cooling capacity

Model name	Rated operating requecy [Hz]	External temperature [°CDB]	Cooling capacity							
			Cold room temperature [°C]							
			-25	-20	-15	-10	-5	0	5	10
LMSEY1A09AVM0* LMSEY1A13AVM0*	50 Hz	45	210	310	410	510	610	710	810	910
		40	240	352	452	553	653	753	854	954
		35	262	377	492	606	709	811	914	1016
		32	268	390	513	636	739	842	945	1048
		30	281	403	526	648	754	860	966	1072
		25	313	432	552	672	783	894	1005	1116
		20	344	461	579	696	812	928	1044	1160
		15	376	490	605	730	841	962	1084	1205
		10	407	527	648	768	888	1009	1129	1249
		5	439	561	683	805	927	1049	1171	1294