



UATYA140-190BFC3Y1



Fh	Orificios de fijación	Ø22	LH	Punto de izado	G..	Soportes de las patas de la compuerta de vibraciones
----	-----------------------	-----	----	----------------	-----	---

Modelo	Peso (kg)						(mm)		
	Envío	Funcionamiento	G1	G2	G3	G4	Gx	Gy	Gz
UATYA140BFC3Y1	3068	3024	390	305	239	306	3200	1188	1101
UATYA150BFC3Y1	3079	3035	368	287	258	332	3192	1108	1100
UATYA160BFC3Y1	3118	3074	379	286	258	342	3155	1107	1098
UATYA180BFC3Y1	3236	3192	380	311	275	337	3234	1117	1101
UATYA190BFC3Y1	3315	3271	395	314	279	351	3195	1116	1065

Modelo	Soportes antivibración de goma				Cajas a pedir *
	G1	G2	G3	G4	
UATYA140BFC3Y1	UATYAAVM2	UATYAAVM1	UATYAAVM1	UATYAAVM1	4 x UATYAAVM1 + 1 x UATYAAVM2
UATYA150BFC3Y1	UATYAAVM2	UATYAAVM1	UATYAAVM1	UATYAAVM1	4 x UATYAAVM1 + 1 x UATYAAVM2
UATYA160BFC3Y1	UATYAAVM2	UATYAAVM1	UATYAAVM1	UATYAAVM1	4 x UATYAAVM1 + 1 x UATYAAVM2
UATYA180BFC3Y1	UATYAAVM2	UATYAAVM1	UATYAAVM1	UATYAAVM1	4 x UATYAAVM1 + 1 x UATYAAVM2
UATYA190BFC3Y1	UATYAAVM2	UATYAAVM1	UATYAAVM1	UATYAAVM2	3 x UATYAAVM1 + 2 x UATYAAVM2

* Cada caja contiene 2 soportes