

Unit combination		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
3xFBQ35D2VEB	RZQSG100L8Y1B	3N~ 50Hz	380~415V	MAX. 50Hz 456V MIN. 50Hz 342V	15.4	16	–	11.4	0.2	0.6	3x0.089	3x0.6
FBQ125D2VEB	RZQSG125L8Y1B				15.2	16	–	11.4	0.2	0.6	0.187	1.5
2xFBQ60D2VEB	RZQSG125L8Y1B				14.7	16	–	11.4	0.2	0.6	2x0.07	2x0.5
3xFBQ50D2VEB	RZQSG125L8Y1B				15.5	16	–	11.4	0.2	0.6	3x0.089	3x0.6
4xFBQ35D2VEB	RZQSG125L8Y1B				16.1	20	–	11.4	0.2	0.6	4x0.089	4x0.6
FBQ140D2VEB	RZQSG140L7Y1B				18.5	20	–	14.2	0.094 + 0.094	0.4 + 0.4	0.187	1.5
2xFBQ71D2VEB	RZQSG140L7Y1B				18	20	–	14.2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBQ50D2VEB	RZQSG140L7Y1B				18.8	20	–	14.2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBQ35D2VEB	RZQSG140L7Y1B				19.4	25	–	14.2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
2xFBQ100D2VEB	RZQ200C7Y1B	3N~ 50Hz	400V	MAX. 50Hz 415V MIN. 50Hz 380V	16	20	–	13.3	0.75	0.7	2x0.127	2x1
3xFBQ71D2VEB	RZQ200C7Y1B				15.5	20	–	13.3	0.75	0.7	3x0.07	3x0.5

Symbols

① Hz

② Voltage

③ Voltage range

MCA Minimum Circuit Ampere [A]

MFA Maximum Fuse Ampere [A]

RLA Rated load amps [A]

OFM Outdoor fan motor

IFM Indoor fan motor

FLA Full Load Ampere (A)

kW Fan motor rated output [kW]

RHz Rated operating frequency [Hz]

COMP Compressor