

RZQG100-140L(8)Y1

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
3xFBQ35D2VEB	RZQG100L8Y1B	3N~ 50Hz	380~ 415V	MAX. 50Hz 456V MIN. 50Hz 342V	18,7	20	–	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
FBQ125D2VEB	RZQG125L8Y1B				18,5	20	–	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBQ60D2VEB	RZQG125L8Y1B				18	20	–	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBQ50D2VEB	RZQG125L8Y1B				18,8	20	–	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBQ35D2VEB	RZQG125L8Y1B				19,4	20	–	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBQ140D2VEB	RZQG140L7Y1B				18,5	20	–	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBQ71D2VEB	RZQG140L7Y1B				18	20	–	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBQ50D2VEB	RZQG140L7Y1B				18,8	20	–	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBQ35D2VEB	RZQG140L7Y1B				19,4	20	–	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6

Notes

- The RLA is based on the following conditions.
Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB
- Select the wire size according to the MCA.
- The maximum allowable voltage that is unbalanced between phases is 2%.
- Use a circuit breaker instead of a fuse.

Symbols

- ① Hz
② Voltage
③ Voltage range
MCA Minimum Circuit Ampere (A)
MFA Maximum Fuse Ampere (A)
RLA Rated load amps [A]

- OFM Outdoor fan motor
IFM Indoor fan motor
FLA Full Load Ampere (A)
kW Fan motor rated output [kW]
RHz Rated operating frequency [Hz]
COMP Compressor

3D094863B