

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
3xFBQ35D2VEB	RZQG100L8Y1B	3N~ 50Hz	380-415V	MAX. 50Hz 456V MIN. 50Hz 342V	18,7	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
FBQ125D2VEB	RZQG125L8Y1B				18,5	20	-	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBQ60D2VEB	RZQG125L8Y1B				18	20	-	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBQ50D2VEB	RZQG125L8Y1B				18,8	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBQ35D2VEB	RZQG125L8Y1B				19,4	20	-	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBQ140D2VEB	RZQG140L7Y1B				18,5	20	-	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBQ71D2VEB	RZQG140L7Y1B				18	20	-	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBQ50D2VEB	RZQG140L7Y1B				18,8	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBQ35D2VEB	RZQG140L7Y1B				19,4	20	-	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBQ100D2VEB	RZQSG100L8Y1B	3N~ 50Hz	380-415V	MAX. 50Hz 456V MIN. 50Hz 342V	14,6	16	-	11,4	0,2	0,6	0,127	1,0
2xFBQ50D2VEB	RZQSG100L8Y1B				14,8	16	-	11,4	0,2	0,6	2x0.089	2x0.6

Symbols

- ① Hz
- ② Voltage
- ③ Voltage range

MCA Minimum Circuit Ampere [A]

MFA Maximum Fuse Ampere [A]

RLA Rated load amps [A]

OFM Outdoor fan motor

IFM Indoor fan motor

FLA Full Load Ampere (A)

kW Fan motor rated output [kW]

RHz Rated operating frequency [Hz]

COMP Compressor