

RZQG100-125L(8)Y1

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	(1)	(2)	(3)	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
3xFBA35A2VEB	RZQG100L8Y1B	3N~ 50Hz	380-415V	MAX. 50Hz 456V MIN. 50Hz 342V	18,7	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
FBA125A2VEB	RZQG125L8Y1B				18,5	20	-	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBA60A2VEB	RZQG125L8Y1B				18	20	-	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBA50A2VEB	RZQG125L8Y1B				18,8	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBA35A2VEB	RZQG125L8Y1B				19,4	20	-	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBA140A2VEB	RZQG140L7Y1B				18,5	20	-	14,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBA71A2VEB	RZQG140L7Y1B				18	20	-	14,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBA50A2VEB	RZQG140L7Y1B				18,8	20	-	14,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBA35A2VEB	RZQG140L7Y1B				19,4	20	-	14,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBA100A2VEB	RZQSG100L8Y1B	3N~ 50Hz	380-415V	MAX. 50Hz 456V MIN. 50Hz 342V	14,6	16	-	11,4	0,2	0,6	0.127	1,0
2xFBA50A2VEB	RZQSG100L8Y1B				14,8	16	-	11,4	0,2	0,6	2x0.089	2x0.6

- Symbols
- ①

Hz
- ②

Voltage
- ③

Voltage range
- MCA

Minimum Circuit Ampere [A]
- MFA

Maximum Fuse Ampere [A]
- RLA

Rated load amps [A]
- OFM

Outdoor fan motor
- IFM

Indoor fan motor
- FLA

Full Load Ampere (A)
- kW

Fan motor rated output [kW]
- RHz

Rated operating frequency [Hz]
- COMP

Compressor