

RZQG125-140L9V1

Indoor	Outdoor	Power supply	Voltage range		MCA	TOCA	MFA	Compressor		OFM		IFM	
								MSC	RLA	kW	FLA	kW	FLA
FCQHG125FVEB		50Hz ~ 220-240V	Minimum: -198 V.	Maximum: 264 V.	29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.244	1.4
FCQG35FVEB	x4				29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.044x4	0.3x4
FCQG50FVEB	x3				28.6	—	32	—	24.2	0.094+0.094	0.4+0.4	0.039x3	0.3x3
FCQG60FVEB	x2				28.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.044x2	0.3x2
FCQG125FVEB					28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.168	1
FFQ35C2VEB	x4				29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050x4	0.4x4
FFQ50C2V1B	x3				29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050x3	0.4x3
FFQ60C2V1B	x2				29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050x2	0.6x2
FDXS35F2VEB	x4				29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.034x4	0.3x4
FDXS50F2VEB9	x3				29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.06x3	0.5x3
FDXS60F2VEB	x2				28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060x2	0.5x2
FBQ35C8VEB	x4				33.5	—	40	—	24.2	0.094+0.094	0.4+0.4	0.140x4	1.2x4
FBQ50C8VEB	x3				32.0	—	40	—	24.2	0.094+0.094	0.4+0.4	0.140x3	1.2x3
FBQ60C8VEB	x2				30.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.350x2	1.1x2
FBQ125C8VEB					30.1	—	32	—	24.2	0.094+0.094	0.4+0.4	0.350	2.1
FDQ125C5VEB					30.1	—	32	—	24.2	0.094+0.094	0.4+0.4	0.350	2.1
FDQ125C7VEB					30.1	—	32	—	24.2	0.094+0.094	0.4+0.4	0.350	2.1
FVQ125CVEB					29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.238	1.2
FHQ35CBVEB	x4				30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x 4	0.6 x 4
FHQ50CBVEB	x3				29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x 3	0.6 x 3
FHQ60CBVEB	x2				29	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x 2	0.6 x 2
FHQ125CBVEB					29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.15	1.5
FUQ125CVEB					29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.106	1.4
FCQHG71FVEB	x2				28.75	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091x2	0.5x2
FCQHG140FVEB					29.25	—	32	—	24.2	0.094+0.094	0.4+0.4	0.244	1.4
FCQG35FVEB	x4				29	—	32	—	24.2	0.094+0.094	0.4+0.4	0.044x4	0.3x4
FCQG50FVEB	x3				28.625	—	32	—	24.2	0.094+0.094	0.4+0.4	0.039x3	0.3x3
FCQG71FVEB	x2				28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.054x2	0.4x2
FCQG140FVEB					28.75	—	32	—	24.2	0.094+0.094	0.4+0.4	0.168	1
FFQ35C2VEB	x4				29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050x4	0.4x4
FFQ50C2VEB	x3				29	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050x3	0.4x3
FDXS35F2VEB	x4				29	—	32	—	24.2	0.094+0.094	0.4+0.4	0.034x4	0.3x4
FDXS50F2VEB9	x3	29.4	—	33	—	25.2	0.094+0.094	0.4+0.4	0.06x3	0.5x3			
FBQ35C8VEB	x4	33.5	—	40	—	24.2	0.094+0.094	0.4+0.4	0.140x4	1.2x4			
FBQ50C8VEB	x3	32	—	40	—	24.2	0.094+0.094	0.4+0.4	0.140x3	1.2x3			
FBQ71C8VEB	x2	30.25	—	32	—	24.2	0.094+0.094	0.4+0.4	0.350x2	1.1x2			
FBQ140C8VEB		30.125	—	32	—	24.2	0.094+0.094	0.4+0.4	0.35	2.1			
FAQ71CVEB9	x2	28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.048x2	0.4x2			
FVQ140CVEB		29.25	—	32	—	24.2	0.094+0.094	0.4+0.4	0.276	1.4			
FHQ35CBVEB	x4	30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x 4	0.6 x 4			
FHQ50CBVEB	x3	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x 3	0.6 x 3			
FHQ71CBVEB	x2	29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x 2	0.8 x 2			
FHQ140CBVEB		29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.15	1.8			
FUQ71CVEB	x2	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.046 x 2	0.9 x 2			

Symbols
MCA: Minimum Circuit Ampere [A]
TOCA: Total overcurrent amps [A]
MFA: Maximum Fuse Ampere [A]
MSC: Maximum current of the starting compressor [A]
RLA: Rated load amps [A]
OFM: Outdoor fan motor
IFM: Indoor fan motor
FLA: Full Load Ampere [A]
KW: Fan motor rated output [kW]