

RZQG125-140L91

Indoor	Outdoor	Power supply	Voltage range	MCA	TOCA	MFA	Compressor		OFM		IFM		
							MSC	RLA	kW	FLA	kW	FLA	
FCAHG71HVEB	x2	RZQG125L9V1B	1~ 50Hz 220-240V	Minimum: 198 V. Maximum: 264 V.	28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x2	0.5 x2
FCAHG140HVEB		RZQG125L9V1B			29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.244	1.4
FCAG35BVEB	x4	RZQG125L9V1B			29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.044 x4	0.3 x4
FCAG50BVEB	x3	RZQG125L9V1B			28.6	—	32	—	24.2	0.094+0.094	0.4+0.4	0.039 x3	0.3 x3
FCAG71BVEB	x2	RZQG125L9V1B			28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.054 x2	0.4 x2
FCAG140BVEB		RZQG125L9V1B			28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.168	1.0
FFA35A2VEB	x4	RZQG125L9V1B			29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050 x4	0.4 x4
FFA50A2VEB	x3	RZQG125L9V1B			29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050 x3	0.4 x3
FBA35A2VEB	x4	RZQG125L9V1B			30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.089 x4	0.6 x4
FBA50A2VEB	x3	RZQG125L9V1B			29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.089 x3	0.6 x3
FBA71A2VEB	x2	RZQG125L9V1B			28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.070 x2	0.5 x2
FBA140A2VEB		RZQG125L9V1B			29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.187	1.5
FHA35AVEB	x4	RZQG125L9V1B			30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x4	0.6 x4
FHA50AVEB	x3	RZQG125L9V1B			29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x3	0.6 x3
FHA71AVEB	x2	RZQG125L9V1B			29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x2	0.8 x2
FHA140AVEB		RZQG125L9V1B			29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.150	1.8
FUA71AVEB	x2	RZQG125L9V1B			29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.046 x2	0.9 x2
FAA71AUVEB	x2	RZQG125L9V1B			28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.048 x2	0.4 x2
FVA140AMVEB		RZQG125L9V1B			29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.276	1.4
FDXM35F3V1B	x4	RZQG125L9V1B			29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.034 x4	0.3 x4
FDXM50F3V1B	x3	RZQG125L9V1B			29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x3	0.5 x3
FCAHG71HVEB	x2	RZQG140L9V1B			28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x2	0.5 x2
FCAHG140HVEB		RZQG140L9V1B			29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.244	1.4
FCAG35BVEB	x4	RZQG140L9V1B			29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.044 x4	0.3 x4
FCAG50BVEB	x3	RZQG140L9V1B			28.6	—	32	—	24.2	0.094+0.094	0.4+0.4	0.039 x3	0.3 x3
FCAG71BVEB	x2	RZQG140L9V1B			28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.054 x2	0.4 x2
FCAG140BVEB		RZQG140L9V1B			28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.168	1.0
FFA35A2VEB	x4	RZQG140L9V1B			29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050 x4	0.4 x4
FFA50A2VEB	x3	RZQG140L9V1B	29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.050 x3	0.4 x3		
FBA35A2VEB	x4	RZQG140L9V1B	30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.089 x4	0.6 x4		
FBA50A2VEB	x3	RZQG140L9V1B	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.089 x3	0.6 x3		
FBA71A2VEB	x2	RZQG140L9V1B	28.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.070 x2	0.5 x2		
FBA140A2VEB		RZQG140L9V1B	29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.187	1.5		
FHA35AVEB	x4	RZQG140L9V1B	30.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x4	0.6 x4		
FHA50AVEB	x3	RZQG140L9V1B	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x3	0.6 x3		
FHA71AVEB	x2	RZQG140L9V1B	29.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.091 x2	0.8 x2		
FHA140AVEB		RZQG140L9V1B	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.150	1.8		
FUA71AVEB	x2	RZQG140L9V1B	29.8	—	32	—	24.2	0.094+0.094	0.4+0.4	0.046 x2	0.9 x2		
FAA71AUVEB	x2	RZQG140L9V1B	28.5	—	32	—	24.2	0.094+0.094	0.4+0.4	0.048 x2	0.4 x2		
FVA140AMVEB		RZQG140L9V1B	29.3	—	32	—	24.2	0.094+0.094	0.4+0.4	0.276	1.4		
FDXM35F3V1B	x4	RZQG140L9V1B	29.0	—	32	—	24.2	0.094+0.094	0.4+0.4	0.034 x4	0.3 x4		
FDXM50F3V1B	x3	RZQG140L9V1B	29.4	—	32	—	24.2	0.094+0.094	0.4+0.4	0.060 x3	0.5 x3		

Symbols

- MCA: Minimum Circuit Ampere [A]
- TOCA: Total overcurrent amps [A]
- MFA: Maximum Fuse Ampere [A]
- MSC: Maximum current of the starting compressor [A]
- RLA: Rated load amps [A]
- OFM: Outdoor fan motor
- IFM: Indoor fan motor
- FLA: Full Load Ampere [A]
- KW: Fan motor rated output [kW]