

Performance characteristics for infrastructure cooling

Cooling

Indoor			Outdoor temperature [°C DB]																										
			-15			-10			-5			0			5			10			15			20					
RH [%]	°CWB	°CDB	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI			
54.5	11.0	16	7.49	6.72	0.33	7.49	6.72	0.34	7.49	6.72	0.35	7.49	6.72	0.36	7.49	6.72	0.37	7.49	6.72	0.38	7.49	6.72	0.38	7.49	6.72	0.38	7.49	6.72	0.38
41.8	11.0	18	7.49	7.49	0.33	7.49	7.49	0.34	7.49	7.49	0.35	7.49	7.49	0.36	7.49	7.49	0.37	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38
57.0	13.0		9.34	7.60	0.42	9.34	7.60	0.43	9.34	7.60	0.44	9.34	7.60	0.45	9.34	7.60	0.45	9.34	7.60	0.45	9.34	7.60	0.45	9.34	7.60	0.45	9.34	7.60	0.45
31.4	11.0	20	7.49	7.49	0.33	7.49	7.49	0.34	7.49	7.49	0.35	7.49	7.49	0.36	7.49	7.49	0.37	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38
44.9	13.0		9.34	8.65	0.42	9.34	8.65	0.43	9.34	8.65	0.44	9.34	8.65	0.45	9.34	8.65	0.45	9.34	8.65	0.45	9.34	8.65	0.45	9.34	8.65	0.45	9.34	8.65	0.45
52.0	14.0	22	10.27	8.56	0.46	10.27	8.56	0.47	10.27	8.56	0.49	10.27	8.56	0.50	10.27	8.56	0.49	10.27	8.56	0.49	10.27	8.56	0.48	10.27	8.56	0.48	10.27	8.56	0.48
22.9	11.0		7.49	7.49	0.33	7.49	7.49	0.34	7.49	7.49	0.35	7.49	7.49	0.36	7.49	7.49	0.37	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38	7.49	7.49	0.38
34.8	13.0	24	9.34	9.34	0.42	9.34	9.34	0.43	9.34	9.34	0.44	9.34	9.34	0.45	9.34	9.34	0.45	9.34	9.34	0.45	9.34	9.34	0.45	9.34	9.34	0.45	9.34	9.34	0.45
47.6	15.0		11.20	9.34	0.51	11.20	9.34	0.52	11.20	9.34	0.53	11.20	9.34	0.55	11.20	9.34	0.54	11.20	9.34	0.52	11.20	9.34	0.51	11.20	9.34	0.51	11.20	9.34	0.51
54.3	16.0	27	12.12	9.00	0.55	12.12	9.00	0.57	12.12	9.00	0.58	12.12	9.00	0.59	12.12	9.00	0.58	12.12	9.00	0.56	12.12	9.00	0.54	12.12	9.00	0.54	12.12	9.00	0.55
21.2	12.0		8.42	8.42	0.37	8.42	8.42	0.38	8.42	8.42	0.39	8.42	8.42	0.41	8.42	8.42	0.41	8.42	8.42	0.41	8.42	8.42	0.41	8.42	8.42	0.41	8.42	8.42	0.41
32.1	14.0	24	10.27	10.27	0.46	10.27	10.27	0.47	10.27	10.27	0.49	10.27	10.27	0.50	10.27	10.27	0.49	10.27	10.27	0.49	10.27	10.27	0.48	10.27	10.27	0.48	10.27	10.27	0.48
43.8	16.0		12.12	10.35	0.55	12.12	10.35	0.57	12.12	10.35	0.58	12.12	10.35	0.59	12.12	10.35	0.58	12.12	10.35	0.56	12.12	10.35	0.54	12.12	10.35	0.54	12.12	10.35	0.55
50.0	17.0	27	12.47	9.38	0.57	12.47	9.38	0.58	12.47	9.38	0.59	12.47	9.38	0.60	12.47	9.38	0.59	12.47	9.38	0.59	12.47	9.38	0.59	12.47	9.38	0.59	12.47	9.38	0.59
21.5	14.0		10.27	10.27	0.46	10.27	10.27	0.47	10.27	10.27	0.49	10.27	10.27	0.50	10.27	10.27	0.49	10.27	10.27	0.49	10.27	10.27	0.48	10.27	10.27	0.48	10.27	10.27	0.48
26.3	15.0	27	11.20	11.20	0.51	11.20	11.20	0.52	11.20	11.20	0.53	11.20	11.20	0.55	11.20	11.20	0.54	11.20	11.20	0.52	11.20	11.20	0.51	11.20	11.20	0.51	11.20	11.20	0.51
31.3	16.0		12.12	12.12	0.55	12.12	12.12	0.57	12.12	12.12	0.58	12.12	12.12	0.59	12.12	12.12	0.58	12.12	12.12	0.56	12.12	12.12	0.54	12.12	12.12	0.54	12.12	12.12	0.55
47.4	19.0	27	13.17	10.18	0.59	13.17	10.18	0.60	13.17	10.18	0.60	13.17	10.18	0.60	13.17	10.18	0.62	13.17	10.18	0.65	13.17	10.18	0.67	13.17	10.18	0.67	13.17	10.18	0.67

Notes

- The ratings shown are net capacities which include a deduction for indoor fan motor heat.
- The capacities are based on the following conditions:
Outdoor air: 85% RH
Corresponding refrigerant piping length: 5.0 m
Level difference: 0m
- For EDP applications, it is recommended to use remote controller setting 16(26)-2-03.
- CPI is a percentage value compared to the rated value which is 1.00.
- The error rate for this value is less than 5% and depends on the indoor unit type.
- The rated power input for each model is mentioned in the table below.

Pair

	FCQHG140F	FCQG140F	FVQ140C	FHQ140C	FBQ140D
Cooling	3,00	3,22	3,74	3,58	3,63

Twin

	FCQHG71Fx2	FCQG71F X 2	FHQ71C X 2	FUQ71C x 2	FAQ71C x 2	FBQ71D X 2
Cooling	2,97	3,17	3,67	3,44	3,69	4,10

Triple

	FCQG50F X 3	FHQ50C X 3	FFQ50C X 3	FDXS50F9 X 3	FBQ50D X 3
Cooling	3,17	3,66	3,23	3,45	3,97

Double twin

	FCQG35F X 4	FHQ35C X 4	FFQ35C X 4	FDXS35F X 4	FBQ35D x 4
Cooling	3,23	3,64	3,01	3,94	3,74

Symbols

- TC: Maximum total cooling capacity [kW]
- SHC: Sensible heat capacity [kW]
- CPI: Coefficient of the power input
- PI: Power input [kW]
compressor + indoor and outdoor fan motors
- RH: Relative humidity [%]