RZQG140L9V1B
RZQG140L8Y1B

Performance characteristics for ·EDP· room

Indoor			Outdoor temperature [°C DB]																																					
			-15			-10			-5			0			5			10			15			20			25			30			35			40		
			TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI	TC	SHC	CPI
RH [%]	°CWB	°CDB	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-	kW	kW	-
54,5	11	16	8,24	7,27	0,32	8,24	7,27	0,33	8,24	7,27	0,34	8,24	7,27	0,35	8,24	7,27	0,37	8,24	7,27	0,37	8,24	7,27	0,37	8,24	7,27	0,38	10,95	8,87	0,96	10,37	8,51	1,06	9,79	8,15	1,16	9,28	7,83	1,25
41,8	11	18	8,24	8,24	0,32	8,24	8,24	0,33	8,24	8,24	0,34	8,24	8,24	0,35	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,38	10,95	9,96	0,96	10,37	9,62	1,06	9,79	9,27	1,16	9,28	8,92	1,25
57,0	13		10,28	8,22	0,41	10,28	8,22	0,42	10,28	8,22	0,43	10,28	8,22	0,45	10,28	8,22	0,45	10,28	8,22	0,44	10,28	8,22	0,44	10,28	8,22	0,44	12,72	9,56	0,97	12,18	9,25	1,07	11,65	8,93	1,17	11,07	8,58	1,26
31,4	11		8,24	8,24	0,32	8,24	8,24	0,33	8,24	8,24	0,34	8,24	8,24	0,35	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,38	10,95	10,95	0,96	10,37	10,37	1,06	9,79	9,79	1,16	9,28	9,28	1,25
44,9	13	20	10,28	9,35	0,41	10,28	9,35	0,42	10,28	9,35	0,43	10,28	9,35	0,45	10,28	9,35	0,45	10,28	9,35	0,44	10,28	9,35	0,44	10,28	9,35	0,44	12,72	10,64	0,97	12,18	10,33	1,07	11,65	10,00	1,17	11,07	9,65	1,26
52,0	14		11,30	9,26	0,45	11,30	9,26	0,47	11,30	9,26	0,48	11,30	9,26	0,49	11,30	9,26	0,49	11,30	9,26	0,48	11,30	9,26	0,47	11,30	9,26	0,47	13,75	10,53	0,97	13,40	10,36	1,07	13,04	10,19	1,17	12,68	9,90	1,27
22,9	11		8,24	8,24	0,32	8,24	8,24	0,33	8,24	8,24	0,34	8,24	8,24	0,35	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,37	8,24	8,24	0,38	10,95	10,95	0,96	10,37	10,37	1,06	9,79	9,79	1,16	9,28	9,28	1,25
34,8	13	22	10,28	10,28	0,41	10,28	10,28	0,42	10,28	10,28	0,43	10,28	10,28	0,45	10,28	10,28	0,45	10,28	10,28	0,44	10,28	10,28	0,44	10,28	10,28	0,44	12,72	12,72	0,97	12,18	12,18	1,07	11,65	11,65	1,17	11,07	11,07	1,26
47,6	15		12,32	10,10	0,50	12,32	10,10	0,51	12,32	10,10	0,52	12,32	10,10	0,54	12,32	10,10	0,53	12,32	10,10	0,51	12,32	10,10	0,50	12,32	10,10	0,50	14,77	11,47	0,98	14,26	11,18	1,08	13,76	10,88	1,18	13,25	10,57	1,27
54,3	16		13,33	9,73	0,54	13,33	9,73	0,56	13,33	9,73	0,57	13,33	9,73	0,58	13,33	9,73	0,57	13,33	9,73	0,55	13,33	9,73	0,53	13,33	9,73	0,54	15,50	10,47	0,98	14,93	10,25	1,08	14,44	10,03	1,18	13,86	9,69	1,28
21,2	12		9,26	9,26	0,37	9,26	9,26	0,38	9,26	9,26	0,39	9,26	9,26	0,40	9,26	9,26	0,41	9,26	9,26	0,41	9,26	9,26	0,41	9,26	9,26	0,41	11,83	11,83	0,97	11,28	11,28	1,07	10,72	10,72	1,17	10,17	10,17	1,25
32,1	14	24	11,30	11,30	0,45	11,30	11,30	0,47	11,30	11,30	0,48	11,30	11,30	0,49	11,30	11,30	0,49	11,30	11,30	0,48	11,30	11,30	0,47	11,30	11,30	0,47	13,75	13,75	0,97	13,40	13,40	1,07	13,04	13,04	1,17	12,68	12,68	1,27
43,8	16		13,33	11,20	0,54	13,33	11,20	0,56	13,33	11,20	0,57	13,33	11,20	0,58	13,33	11,20	0,57	13,33	11,20	0,55	13,33	11,20	0,53	13,33	11,20	0,54	15,50	12,14	0,98	14,93	11,86	1,08	14,44	11,62	1,18	13,86	11,30	1,28
50,0	17		13,72	10,15	0,56	13,72	10,15	0,57	13,72	10,15	0,58	13,72	10,15	0,59	13,72	10,15	0,58	13,72	10,15	0,58	13,72	10,15	0,58	13,72	10,15	0,58	16,23	11,78	0,98	15,53	11,43	1,08	14,83	11,06	1,18	14,14	10,63	1,29
21,5	14		11,30	11,30	0,45	11,30	11,30	0,47	11,30	11,30	0,48	11,30	11,30	0,49	11,30	11,30	0,49	11,30	11,30	0,48	11,30	11,30	0,47	11,30	11,30	0,47	13,75	13,75	0,97	13,40	13,40	1,07	13,04	13,04	1,17	12,68	12,68	1,27
26,3	15	27	12,32	12,32	0,50	12,32	12,32	0,51	12,32	12,32	0,52	12,32	12,32	0,54	12,32	12,32	0,53	12,32	12,32	0,51	12,32	12,32	0,50	12,32	12,32	0,50	14,77	14,77	0,98	14,26	14,26	1,08	13,76	13,76	1,18	13,25	13,25	1,27
31,3	16		13,33	13,33	0,54	13,33	13,33	0,56	13,33	13,33	0,57	13,33	13,33	0,58	13,33	13,33	0,57	13,33	13,33	0,55	13,33	13,33	0,53	13,33	13,33	0,54	15,50	15,50	0,98	14,93	14,93	1,08	14,44	14,44	1,18	13,86	13,86	1,28

Pair	FCQHG140F	FCQG140F	FVQ140C	FHQ140C	FBQ140D
	FCAHG140H	FCAG140B	FVA140A	FHA140A	FBA140A
Cooling	4,00	4,17	4,17	4,05	4,00

Twin	FCQHG71F X 2	FCQG71F X 2	FHQ71C X 2	FUQ71C X 2	FAQ71C X 2	FBQ71D X 2
	FCAHG71H X 2	FCAG71B X 2	FHA71A9 X 2	FUA71A X 2	FAA71B X 2	FBA71A9 X 2
Cooling	3,94	4,11	3,59	3,35	3,81	3,75

Triple	FCQG50F X 3	FHQ50C X 3	FFQ50C X 3	FDXS50F9 X 3	FBQ50D X 3
	FCAG50B X 3	FHA50A9 X 3	FFA50A9 X 3	FDXM50F9 X 3	FBA50A9 X 3
Cooling	4,12	4,25	4,15	4,26	3,75

Double twin	FCQG35F X 4	FHQ35C X 4	FFQ35C X 4	FDXS35F X 4	FBQ35D X 4
	FCAG35B X 4	FHA35A9 X 4	FFA35A9 X 4	FDXM35F9 X 4	FBA35A9 X 4
Cooling	4,18	4,23	3,83	5,38	3,75

Symbols

TC: Maximum total cooling capacity [kW]
SHC: Sensible heat capacity [kW]
CPI: Coefficient of the power input
PI: Power input [kW]
compressor + indoor and outdoor fan motors
RH: Relative humidity [%]

Notes

1. The ratings shown are net capacities which include a deduction for indoor fan motor heat.
2. The capacities are based on the following conditions:
   Outdoor air: ·85% RH·
   Corresponding refrigerant piping length: ·5.0· m
   Level difference: ·0·m
3. For ·EDP· applications, it is recommended to use remote controller setting ·16(26)-2-03·.
4. ·CPI· is a percentage value compared to the rated value which is ·1.00·.
5. The error rate for this value is less than ·5·% and depends on the indoor unit type.
6. The rated power input for each model is mentioned in the table below.