

Unit combination restrictions		Power supply				COMP				OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA	
2xFBQ60D2VEB	RZQSG125L9V1B	50	220~240V	MAX. 50Hz 264V MIN. 50Hz 198V	29	32	–	24.4	0.2	0.6	2x0.07	2x0.5	
3xFBQ50D2VEB	RZQSG125L9V1B				29.8	32	–	24.4	0.2	0.6	3x0.089	3x0.6	
4xFBQ35D2VEB	RZQSG125L9V1B				30.4	32	–	24.4	0.2	0.6	4x0.089	4x0.6	
FBQ140D2VEB	RZQSG140L9V1B				29.5	32	74	24.2	0.094 + 0.094	0.4 + 0.4	0.187	1.5	
2xFBQ71D2VEB	RZQSG140L9V1B				29	32	–	24.2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5	
3xFBQ50D2VEB	RZQSG140L9V1B				29.8	32	–	24.2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6	
4xFBQ35D2VEB	RZQSG140L9V1B				30.4	32	–	24.2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6	
FBQ71D2VEB	RZQG71L8Y1B				3N~ 50Hz	380~415V	MAX. 50Hz 456V MIN. 50Hz 342V	11.8	16	–	9.6	0.094	0.4
2xFBQ35D2VEB	RZQG71L8Y1B	12	16	–				9.6	0.094	0.4	2x0.089	2x0.6	
FBQ100D2VEB	RZQG100L8Y1B	17.9	20	–				14.2	0.094 + 0.094	0.4 + 0.4	0.127	1.0	
2xFBQ50D2VEB	RZQG100L8Y1B	18.1	20	–				14.2	0.094 + 0.094	0.4 + 0.4	2x0.089	2x0.6	

- Symbols
- ①

Hz
- ②

Voltage
- ③

Voltage range
- MCA

Minimum Circuit Ampere [A]
- MFA

Maximum Fuse Ampere [A]
- RLA

Rated load amps [A]
- OFM

Outdoor fan motor
- IFM

Indoor fan motor
- FLA

Full Load Ampere (A)
- kW

Fan motor rated output [kW]
- RHz

Rated operating frequency [Hz]
- COMP

Compressor