

Unit combination restrictions		Power supply				COMP		OFM		IFM		
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
2xFBA60A2VEB	RZQSG125L9V1B	50	220~240V	MAX. 50Hz 264V MIN. 50Hz 198V	29	32	–	24,4	0,2	0,6	2x0.07	2x0.5
3xFBA50A2VEB	RZQSG125L9V1B				29,8	32	–	24,4	0,2	0,6	3x0.089	3x0.6
4xFBA35A2VEB	RZQSG125L9V1B				30,4	32	–	24,4	0,2	0,6	4x0.089	4x0.6
FBA140A2VEB	RZQSG140L9V1B				29,5	32	74	24,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBA71A2VEB	RZQSG140L9V1B				29	32	–	24,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBA50A2VEB	RZQSG140L9V1B				29,8	32	–	24,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBA35A2VEB	RZQSG140L9V1B				30,4	32	–	24,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBA71A2VEB	RZQG71L8Y1B	3N~ 50Hz	380~415V	MAX. 50Hz 456V MIN. 50Hz 342V	11,8	16	–	9,6	0,094	0,4	0,07	0,5
2xFBA35A2VEB	RZQG71L8Y1B				12	16	–	9,6	0,094	0,4	2x0.089	2x0.6
FBA100A2VEB	RZQG100L8Y1B				17,9	20	–	14,2	0.094 + 0.094	0.4 + 0.4	0,127	1,0
2xFBA50A2VEB	RZQG100L8Y1B				18,1	20	–	14,2	0.094 + 0.094	0.4 + 0.4	2x0.089	2x0.6

Symbols

①

Hz

②

Voltage

③

Voltage range

MCA

Minimum Circuit Ampere [A]

MFA

Maximum Fuse Ampere [A]

RLA

Rated load amps [A]

OFM

Outdoor fan motor

IFM

Indoor fan motor

FLA

Full Load Ampere (A)

kW

Fan motor rated output [kW]

RHz

Rated operating frequency [Hz]

COMP

Compressor