

RZQSG125-140L9V1

Unit combination restrictions		Power supply			COMP				OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
2xFBA60A2VEB	RZQSG125L9V1B	50	220-240V	MAX. 50Hz 264V MIN. 50Hz 198V	29	32	-	24,4	0,2	0,6	2x0.07	2x0.5
3xFBA50A2VEB	RZQSG125L9V1B				29,8	32	-	24,4	0,2	0,6	3x0.089	3x0.6
4xFBA35A2VEB	RZQSG125L9V1B				30,4	32	-	24,4	0,2	0,6	4x0.089	4x0.6
FBA140A2VEB	RZQSG140L9V1B				29,5	32	74	24,2	0.094 + 0.094	0.4 + 0.4	0,187	1,5
2xFBA71A2VEB	RZQSG140L9V1B				29	32	-	24,2	0.094 + 0.094	0.4 + 0.4	2x0.07	2x0.5
3xFBA50A2VEB	RZQSG140L9V1B				29,8	32	-	24,2	0.094 + 0.094	0.4 + 0.4	3x0.089	3x0.6
4xFBA35A2VEB	RZQSG140L9V1B				30,4	32	-	24,2	0.094 + 0.094	0.4 + 0.4	4x0.089	4x0.6
FBA71A2VEB	RZQG71L8Y1B				3N~ 50Hz	380-415V	MAX. 50Hz 456V MIN. 50Hz 342V	11,8	16	-	9,6	0,094
2xFBA35A2VEB	RZQG71L8Y1B	12	16	-				9,6	0,094	0,4	2x0.089	2x0.6
FBA100A2VEB	RZQG100L8Y1B	17,9	20	-				14,2	0.094 + 0.094	0.4 + 0.4	0,127	1,0
2xFBA50A2VEB	RZQG100L8Y1B	18,1	20	-				14,2	0.094 + 0.094	0.4 + 0.4	2x0.089	2x0.6

Symbols

- ① Hz
- ② Voltage
- ③ Voltage range

MCA Minimum Circuit Ampere [A]

MFA Maximum Fuse Ampere [A]

RLA Rated load amps [A]

OFM Outdoor fan motor

IFM Indoor fan motor

FLA Full Load Ampere (A)

kW Fan motor rated output [kW]

RHz Rated operating frequency [Hz]

COMP Compressor