

2MXM40A

Cooling ·230V 50Hz·

| Outdoor unit | Indoor unit | Cooling capacity [kW] | | Total capacity [kW] | | | Power input [kW] | | | Total current [A] | | | Power factor [%] |
|---|-------------|-----------------------|----------|---------------------|---------|---------|------------------|---------|---------|-------------------|---------|---------|------------------|
| | | Room ·A· | Room ·B· | Minimum | Nominal | Maximum | Minimum | Nominal | Maximum | Minimum | Nominal | Maximum | |
| 2MXM40M2V1B 2MXM40M3V1B 2MXM40M4V1B 2MXM40N2V1B 2MXM40N2V1B9 2MXM40A2V1B | 1.5 | 1,50 | - | 1,30 | 1,50 | 2,00 | 0,33 | 0,31 | 0,40 | 1,78 | 1,70 | 2,17 | 79 |
| | 2.0 | 2,00 | - | 1,30 | 2,00 | 2,40 | 0,33 | 0,44 | 0,57 | 1,78 | 2,38 | 3,09 | 79 |
| | 2.5 | 2,50 | - | 1,30 | 2,50 | 3,00 | 0,33 | 0,61 | 0,80 | 1,78 | 3,33 | 4,40 | 79 |
| | 3.5 | 3,50 | - | 1,30 | 3,50 | 4,00 | 0,33 | 1,04 | 1,35 | 1,78 | 5,71 | 7,38 | 79 |
| | 1.5+1.5 | 1,50 | 1,50 | 1,50 | 3,00 | 3,60 | 0,31 | 0,60 | 0,73 | 1,67 | 3,33 | 4,00 | 79 |
| | 1.5+2.0 | 1,50 | 2,00 | 1,50 | 3,50 | 4,00 | 0,31 | 0,79 | 0,91 | 1,67 | 4,35 | 4,98 | 79 |
| | 1.5+2.5 | 1,50 | 2,50 | 1,50 | 4,00 | 4,20 | 0,31 | 0,98 | 1,03 | 1,67 | 5,37 | 5,64 | 79 |
| | 1.5+3.5 | 1,20 | 2,80 | 1,50 | 4,00 | 4,40 | 0,31 | 0,96 | 1,06 | 1,67 | 5,30 | 5,83 | 79 |
| | 2.0+2.0 | 2,00 | 2,00 | 1,50 | 4,00 | 4,20 | 0,31 | 0,97 | 1,02 | 1,67 | 5,34 | 5,61 | 79 |
| | 2.0+2.5 | 1,78 | 2,22 | 1,50 | 4,00 | 4,30 | 0,31 | 0,96 | 1,04 | 1,67 | 5,30 | 5,70 | 79 |
| | 2.0+3.5 | 1,45 | 2,55 | 1,50 | 4,00 | 4,50 | 0,31 | 0,95 | 1,08 | 1,67 | 5,25 | 5,91 | 79 |
| | 2.5+2.5 | 2,00 | 2,00 | 1,50 | 4,00 | 4,40 | 0,31 | 0,96 | 1,06 | 1,67 | 5,27 | 5,80 | 79 |
| 2.5+3.5 | 1,67 | 2,33 | 1,50 | 4,00 | 4,60 | 0,31 | 0,94 | 1,09 | 1,67 | 5,20 | 5,98 | 79 | |

Notes

- 1) The total capacity of each connected indoor unit is up to ·6·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5· kW class
Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series
- 3) Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.