

Notes

- 1) The total capacity of each connected indoor unit is up to ·8.5·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
 - 1.5, 2.0, 2.5, 3.5, 4.2, 5.0· kW class
 - Wall-mounted ·CTXA-AS, CXTA-AT, CXTA-AW, CXTA-BB, CXTA-BS, CXTA-BT, CXTA-CW, CXTA-CB, CXTA-CS, CXTA-DG, CXTA-DP, CXTA-DL, CXTA-DC, CXTA-DY, CXTM-A, CXTM-M, CXTM-N, CXTM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXA-CW, FTXA-CB, FTXA-CS, FTXA-DG, FTXA-DP, FTXA-DL, FTXA-DC, FTXA-DY, FTXM-A, FTXM-M, FTXM-N, FTXM-R, FTXJ-AB, FTXJ-AS, FTXJ-AW, FTXJ-AW9, FTXJ-AB9, FTXJ-AS9· series
- 3) Heating capacity conditions
 - Indoor temperature ·20·°C DB
 - Outdoor temperature ·7·°C DB / ·6·°C WB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.