

Heating ·230V 50Hz·

Outdoor unit	Indoor unit	Heating capacity [kW]					Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Room ·D·	Room ·E·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
5MXM90M2V1B 5MXM90N2V1B 5MXM90N2V1B9 5MXM90A2V1B	2.0+2.0+3.5+3.5+4.2	1,32	1,32	2,30	2,30	2,76	5,00	10,00	11,67	0,79	2,03	2,52	3,70	9,40	11,52	95
	2.0+2.5+2.5+2.5+2.5	1,67	2,08	2,08	2,08	2,08	4,20	10,00	11,66	0,65	2,04	2,52	3,00	9,40	11,60	95
	2.0+2.5+2.5+2.5+3.5	1,54	1,92	1,92	1,92	2,69	4,36	10,00	11,66	0,67	2,04	2,52	3,20	9,40	11,60	95
	2.0+2.5+2.5+2.5+4.2	1,46	1,82	1,82	1,82	3,07	4,68	10,00	11,67	0,73	2,03	2,52	3,40	9,30	11,51	95
	2.0+2.5+2.5+2.5+5.0	1,38	1,72	1,72	1,72	3,45	4,82	10,00	11,71	0,75	2,02	2,53	3,50	9,30	11,60	95
	2.0+2.5+2.5+2.5+6.0	1,29	1,61	1,61	1,61	3,87	5,14	10,00	11,97	0,81	2,02	2,62	3,80	9,30	12,10	95
	2.0+2.5+2.5+3.5+3.5	1,43	1,79	1,79	2,50	2,50	4,68	10,00	11,66	0,73	2,04	2,52	3,40	9,40	11,60	95
	2.0+2.5+2.5+3.5+4.2	1,36	1,70	1,70	2,38	2,86	5,00	10,00	11,67	0,79	2,03	2,52	3,70	9,30	11,51	95
	2.0+2.5+2.5+3.5+5.0	1,29	1,61	1,61	2,26	3,23	5,14	10,00	11,71	0,81	2,02	2,53	3,80	9,30	11,60	95
	2.0+2.5+2.5+4.2+4.2	1,30	1,62	1,62	2,73	2,73	5,15	10,00	11,62	0,81	2,03	2,50	3,80	9,30	11,50	95
	2.0+2.5+3.5+3.5+3.5	1,33	1,67	2,33	2,33	2,33	5,00	10,00	11,66	0,79	2,04	2,52	3,70	9,40	11,60	95
	2.5+2.5+2.5+2.5+2.5	2,00	2,00	2,00	2,00	2,00	4,36	10,00	11,65	0,67	2,04	2,52	3,20	9,40	11,60	95
	2.5+2.5+2.5+2.5+3.5	1,85	1,85	1,85	1,85	2,59	4,52	10,00	11,65	0,70	2,04	2,52	3,30	9,40	11,60	95
	2.5+2.5+2.5+2.5+4.2	1,76	1,76	1,76	1,76	2,96	4,83	10,00	11,66	0,76	2,03	2,51	3,50	9,30	11,49	95
	2.5+2.5+2.5+2.5+5.0	1,67	1,67	1,67	1,67	3,33	4,98	10,00	11,70	0,78	2,02	2,53	3,70	9,30	11,60	95
	2.5+2.5+2.5+3.5+3.5	1,72	1,72	1,72	2,41	2,41	4,84	10,00	11,65	0,76	2,04	2,52	3,50	9,40	11,60	95
	2.5+2.5+2.5+3.5+4.2	1,64	1,64	1,64	2,30	2,76	4,99	10,00	11,67	0,79	2,03	2,51	3,70	9,30	11,50	95
	2.5+2.5+3.5+3.5+3.5	1,61	1,61	2,26	2,26	2,26	5,16	10,00	11,69	0,82	2,04	2,53	3,80	9,40	11,57	95

Notes

- 1) The total capacity of each connected indoor unit is up to ·15.6 kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0, 7.1· kW class
Wall-mounted ·CTXA-AS, CTXA-AT, CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXM-M, CTXM-N, CTXM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXM-M, FTXM-N, FTXM-R, FTJX-AB, FTJX-AS, FTJX-AW· series
- 3) Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.