

# 3MXM52A

Cooling ·230V 50Hz·

Outdoor unit	Indoor unit	Cooling capacity [kW]			Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
3MXM52N2V1B 3MXM52N2V1B9 3MXM52N2V1B8 3MXM52N2V1B7 3MXM52A2V1B	1.5	1,50	-	-	1,40	1,50	2,40	0,34	0,36	0,63	1,50	1,62	2,86	96
	2.0	2,00	-	-	1,60	2,00	3,00	0,36	0,48	0,78	1,60	2,17	3,51	96
	2.5	2,50	-	-	1,60	2,50	3,20	0,36	0,64	0,87	1,62	2,89	3,92	96
	3.5	3,50	-	-	1,60	3,50	4,20	0,37	0,98	1,30	1,63	4,43	5,88	96
	4.2	4,20	-	-	1,60	4,20	4,80	0,37	1,21	1,55	1,63	5,47	7,04	96
	5.0	5,00	-	-	1,60	5,00	5,40	0,35	1,76	2,03	1,55	7,94	9,18	96
	1.5+1.5	1,50	1,50	-	1,70	3,00	4,70	0,35	0,55	1,32	1,55	2,50	5,98	96
	1.5+2.0	1,50	2,00	-	1,70	3,50	4,70	0,35	0,66	1,30	1,55	2,99	5,88	96
	1.5+2.5	1,50	2,50	-	1,70	4,00	5,00	0,35	0,78	1,92	1,55	3,54	8,66	96
	1.5+3.5	1,50	3,50	-	1,70	5,00	6,00	0,35	1,06	2,17	1,55	4,81	9,80	96
	1.5+4.2	1,37	3,83	-	1,70	5,20	6,10	0,35	1,10	2,26	1,55	4,99	10,21	96
	1.5+5.0	1,20	4,00	-	1,80	5,20	6,30	0,37	1,10	2,28	1,68	4,99	10,31	96
	2.0+2.0	2,00	2,00	-	1,80	4,00	5,10	0,37	0,85	1,91	1,68	3,85	8,66	96
	2.0+2.5	2,00	2,50	-	1,80	4,50	5,30	0,37	0,95	1,89	1,68	4,31	8,56	96
	2.0+3.5	1,89	3,31	-	1,80	5,20	6,30	0,37	1,10	2,30	1,68	4,99	10,38	96
	2.0+4.2	1,68	3,52	-	1,80	5,20	6,30	0,37	1,09	2,25	1,68	4,94	10,18	96
	2.0+5.0	1,49	3,71	-	1,80	5,20	6,50	0,37	1,09	2,19	1,68	4,94	9,89	96
	2.5+2.5	2,50	2,50	-	1,80	5,00	6,00	0,37	1,04	2,23	1,68	4,72	10,09	96
	2.5+3.5	2,17	3,03	-	1,80	5,20	6,10	0,37	1,09	2,21	1,68	4,94	10,00	96
	2.5+4.2	1,94	3,26	-	1,80	5,20	6,40	0,37	1,09	2,30	1,68	4,94	10,41	96
	2.5+5.0	1,73	3,47	-	1,80	5,20	6,50	0,37	1,06	2,14	1,68	4,81	9,68	96
	3.5+3.5	2,60	2,60	-	1,80	5,20	6,40	0,37	1,08	2,28	1,68	4,90	10,31	96
	3.5+4.2	2,36	2,84	-	1,80	5,20	6,40	0,37	1,08	2,26	1,68	4,90	10,21	96
	3.5+5.0	2,14	3,06	-	1,80	5,20	6,60	0,37	1,06	2,19	1,68	4,81	9,89	96
	4.2+4.2	2,60	2,60	-	1,80	5,20	6,50	0,37	1,07	2,24	1,68	4,85	10,11	96
	1.5+1.5+1.5	1,50	1,50	1,50	1,80	4,50	6,40	0,37	0,90	2,18	1,65	4,08	9,86	96
	1.5+1.5+2.0	1,44	1,44	1,92	1,80	4,80	6,40	0,37	1,02	2,16	1,65	4,61	9,78	96
	1.5+1.5+2.5	1,42	1,42	2,36	1,80	5,20	6,70	0,37	1,09	2,23	1,65	4,94	10,10	96
	1.5+1.5+3.5	1,20	1,20	2,80	1,90	5,20	6,80	0,37	1,09	2,28	1,65	4,94	10,30	96
	1.5+1.5+4.2	1,08	1,08	3,03	1,90	5,20	6,80	0,37	1,08	2,26	1,65	4,90	10,20	96
	1.5+1.5+5.0	0,98	0,98	3,25	1,90	5,20	7,10	0,33	1,05	2,17	1,51	4,76	9,80	96
	1.5+2.0+2.0	1,42	1,89	1,89	1,80	5,20	6,45	0,37	1,10	2,13	1,65	4,99	9,64	96
	1.5+2.0+2.5	1,30	1,73	2,17	1,80	5,20	6,70	0,37	1,09	2,19	1,65	4,94	9,90	96
	1.5+2.0+3.5	1,11	1,49	2,60	1,90	5,20	6,80	0,37	1,08	2,23	1,65	4,90	10,10	96
	1.5+2.0+4.2	1,01	1,35	2,84	1,90	5,20	6,80	0,37	1,08	2,19	1,65	4,90	9,90	96
	1.5+2.0+5.0	0,92	1,22	3,06	1,90	5,20	7,20	0,33	1,04	2,15	1,51	4,72	9,70	96
	1.5+2.5+2.5	1,20	2,00	2,00	1,80	5,20	6,70	0,37	1,09	2,17	1,65	4,94	9,80	96
	1.5+2.5+3.5	1,04	1,73	2,43	1,90	5,20	6,80	0,37	1,08	2,21	1,65	4,90	10,00	96
	1.5+2.5+4.2	0,95	1,59	2,66	1,90	5,20	6,80	0,37	1,07	2,19	1,65	4,85	9,90	96
	1.5+2.5+5.0	0,87	1,44	2,89	1,90	5,20	7,30	0,33	1,04	2,17	1,51	4,72	9,80	96
1.5+3.5+3.5	0,92	2,14	2,14	1,80	5,20	7,30	0,37	1,07	2,15	1,65	4,85	9,70	96	
2.0+2.0+2.0	1,73	1,73	1,73	1,80	5,20	6,50	0,37	1,07	2,06	1,65	4,85	9,34	96	
2.0+2.0+2.5	1,60	1,60	2,00	1,80	5,20	7,00	0,37	1,06	2,21	1,65	4,81	10,00	96	
2.0+2.0+3.5	1,39	1,39	2,43	1,90	5,20	7,20	0,39	1,05	2,17	1,75	4,76	9,80	96	
2.0+2.0+4.2	1,27	1,27	2,66	1,90	5,20	7,20	0,39	1,04	2,15	1,75	4,72	9,70	96	
2.0+2.0+5.0	1,16	1,16	2,89	1,90	5,20	7,30	0,35	1,03	2,19	1,59	4,67	9,91	96	
2.0+2.5+2.5	1,49	1,86	1,86	1,80	5,20	7,10	0,39	1,05	2,12	1,75	4,76	9,60	96	
2.0+2.5+3.5	1,30	1,63	2,28	1,90	5,20	7,20	0,39	1,04	2,15	1,75	4,72	9,70	96	
2.0+2.5+4.2	1,20	1,49	2,51	1,90	5,20	7,20	0,39	1,04	2,14	1,75	4,72	9,65	96	
2.0+3.5+3.5	1,16	2,02	2,02	1,90	5,20	7,30	0,39	1,04	2,15	1,75	4,72	9,70	96	
2.5+2.5+2.5	1,73	1,73	1,73	1,90	5,20	7,10	0,39	1,04	2,19	1,75	4,72	9,90	96	
2.5+2.5+3.5	1,53	1,53	2,14	1,90	5,20	7,20	0,39	1,04	2,16	1,75	4,72	9,75	96	

**Notes**

- The total capacity of each connected indoor unit is up to ·9.0·kW.
- The values mentioned in this document are for connecting with the following indoor unit types:  
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0· kW class  
Wall-mounted ·CTXA-AS, CTXA-AT, CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXM-M, CTXM-N, CTXM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXM-M, FTXM-N, FTXM-R, FTXJ-AB, FTXJ-AS, FTXJ-AW· series
- Cooling capacity conditions  
Indoor temperature ·27·°C DB / ·19·°C WB  
Outdoor temperature ·35·°C DB
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.