

4MXM80A

Heating · 230V 50Hz

Outdoor unit	Indoor unit	Heating capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room · A	Room · B	Room · C	Room · D	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
	2.0+2.0+2.0+5.0	1,75	1,75	1,75	4,36	3,69	9,60	11,30	0,59	2,04	2,57	2,80	9,40	11,90	95
	2.0+2.0+2.0+6.0	1,60	1,60	1,60	4,80	4,01	9,60	11,51	0,64	2,03	2,65	3,00	9,40	12,13	95
	2.0+2.0+2.0+7.1	1,47	1,47	1,47	5,20	4,33	9,60	11,57	0,70	2,03	2,66	3,30	9,30	12,20	95
	2.0+2.0+2.5+2.5	2,13	2,13	2,67	2,67	3,23	9,60	11,15	0,52	2,13	2,64	2,40	9,80	12,10	95
	2.0+2.0+2.5+3.5	1,92	1,92	2,40	3,36	3,39	9,60	11,15	0,54	2,13	2,64	2,60	9,80	12,10	95
	2.0+2.0+2.5+4.2	1,79	1,79	2,24	3,77	3,55	9,60	11,23	0,57	2,10	2,64	2,70	9,60	12,07	95
	2.0+2.0+2.5+5.0	1,67	1,67	2,09	4,17	3,85	9,60	11,30	0,61	2,03	2,57	2,90	9,40	11,80	95
	2.0+2.0+2.5+6.0	1,54	1,54	1,92	4,61	4,17	9,60	11,51	0,67	2,03	2,64	3,20	9,30	12,10	95
	2.0+2.0+2.5+7.1	1,41	1,41	1,76	5,01	4,49	9,60	11,57	0,73	2,02	2,65	3,40	9,30	12,20	95
	2.0+2.0+3.5+3.5	1,75	1,75	3,05	3,05	3,72	9,60	11,22	0,60	2,13	2,67	2,80	9,80	12,24	95
	2.0+2.0+3.5+4.2	1,64	1,64	2,87	3,45	3,87	9,60	11,23	0,63	2,10	2,64	2,90	9,60	12,07	95
	2.0+2.0+3.5+5.0	1,54	1,54	2,69	3,84	4,17	9,60	11,30	0,67	2,03	2,57	3,20	9,40	11,80	95
	2.0+2.0+3.5+6.0	1,42	1,42	2,49	4,27	4,33	9,60	11,51	0,70	2,03	2,64	3,30	9,30	12,10	95
	2.0+2.0+4.2+4.2	1,55	1,55	3,25	3,25	4,02	9,60	11,24	0,65	2,07	2,60	3,00	9,50	11,91	95
	2.0+2.0+4.2+5.0	1,45	1,45	3,05	3,64	4,33	9,60	11,37	0,70	2,01	2,57	3,30	9,30	11,78	95
	2.0+2.0+4.2+6.0	1,35	1,35	2,84	4,06	4,65	9,60	11,57	0,75	2,01	2,63	3,50	9,30	12,10	95
	2.0+2.0+5.0+5.0	1,37	1,37	3,43	3,43	4,48	9,60	11,48	0,72	1,98	2,56	3,30	9,10	11,74	95
	2.0+2.5+2.5+2.5	2,02	2,53	2,53	2,53	3,23	9,60	11,15	0,52	2,12	2,63	2,40	9,80	12,10	95
	2.0+2.5+2.5+3.5	1,83	2,29	2,29	3,20	3,55	9,60	11,15	0,57	2,12	2,63	2,70	9,80	12,10	95
	2.0+2.5+2.5+4.2	1,71	2,14	2,14	3,60	3,71	9,60	11,16	0,60	2,09	2,59	2,80	9,60	11,90	95
4MXM80M2V1B 4MXM80N2V1B 4MXM80N2V1B9 4MXM80A2V1B	2.0+2.5+2.5+5.0	1,60	2,00	2,00	4,00	4,01	9,60	11,30	0,64	2,03	2,56	3,00	9,30	11,80	95
	2.0+2.5+2.5+6.0	1,48	1,85	1,85	4,43	4,17	9,60	11,51	0,67	2,02	2,64	3,10	9,30	12,08	95
	2.0+2.5+2.5+7.1	1,36	1,70	1,70	4,83	4,49	9,60	11,57	0,73	2,02	2,65	3,40	9,30	12,20	95
	2.0+2.5+3.5+3.5	1,67	2,09	2,92	2,92	3,88	9,60	11,23	0,63	2,12	2,67	2,90	9,80	12,20	95
	2.0+2.5+3.5+4.2	1,57	1,97	2,75	3,30	4,03	9,60	11,23	0,65	2,09	2,63	3,10	9,60	12,04	95
	2.0+2.5+3.5+5.0	1,48	1,85	2,58	3,69	4,17	9,60	11,30	0,67	2,03	2,56	3,20	9,30	11,80	95
	2.0+2.5+3.5+6.0	1,37	1,71	2,40	4,11	4,49	9,60	11,51	0,73	2,02	2,64	3,40	9,30	12,08	95
	2.0+2.5+4.2+4.2	1,49	1,86	3,13	3,13	4,18	9,60	11,24	0,68	2,07	2,60	3,20	9,50	11,88	95
	2.0+2.5+4.2+5.0	1,40	1,75	2,94	3,50	4,49	9,60	11,37	0,73	2,01	2,57	3,40	9,30	11,76	95
	2.0+2.5+5.0+5.0	1,32	1,66	3,31	3,31	4,63	9,60	11,48	0,75	1,99	2,56	3,50	9,20	11,72	95
	2.0+3.5+3.5+3.5	1,54	2,69	2,69	2,69	4,20	9,60	11,23	0,69	2,12	2,67	3,20	9,80	12,20	95
	2.0+3.5+3.5+4.2	1,45	2,55	2,55	3,05	4,35	9,60	11,23	0,71	2,09	2,63	3,30	9,60	12,04	95
	2.0+3.5+3.5+5.0	1,37	2,40	2,40	3,43	4,49	9,60	11,37	0,73	2,03	2,60	3,40	9,30	11,88	95
	2.0+3.5+4.2+4.2	1,38	2,42	2,90	2,90	4,50	9,60	11,24	0,74	2,07	2,60	3,40	9,50	11,88	95
	2.5+2.5+2.5+2.5	2,40	2,40	2,40	2,40	3,39	9,60	11,16	0,54	2,11	2,62	2,60	9,70	12,10	95
	2.5+2.5+2.5+3.5	2,18	2,18	2,18	3,05	3,71	9,60	11,16	0,60	2,11	2,62	2,80	9,70	12,10	95
	2.5+2.5+2.5+4.2	2,05	2,05	2,05	3,45	3,87	9,60	11,16	0,62	2,09	2,59	2,90	9,60	11,90	95
	2.5+2.5+2.5+5.0	1,92	1,92	1,92	3,84	4,17	9,60	11,30	0,67	2,03	2,55	3,10	9,30	11,80	95
	2.5+2.5+2.5+6.0	1,78	1,78	1,78	4,27	4,33	9,60	11,51	0,70	2,02	2,63	3,30	9,30	12,05	95
	2.5+2.5+3.5+3.5	2,00	2,00	2,80	2,80	4,03	9,60	11,23	0,66	2,11	2,66	3,10	9,70	12,17	95
2.5+2.5+3.5+4.2	1,89	1,89	2,65	3,17	4,19	9,60	11,23	0,68	2,09	2,62	3,20	9,60	12,00	95	
2.5+2.5+3.5+5.0	1,78	1,78	2,49	3,56	4,33	9,60	11,30	0,70	2,03	2,55	3,30	9,30	11,80	95	
2.5+2.5+3.5+6.0	1,66	1,66	2,32	3,97	4,65	9,60	11,51	0,76	2,02	2,63	3,50	9,30	12,05	95	
2.5+2.5+4.2+4.2	1,79	1,79	3,01	3,01	4,34	9,60	11,24	0,71	2,06	2,59	3,30	9,50	11,85	95	
2.5+2.5+4.2+5.0	1,69	1,69	2,84	3,38	4,65	9,60	11,37	0,75	2,01	2,56	3,50	9,20	11,73	95	
2.5+3.5+3.5+3.5	1,85	2,58	2,58	2,58	4,20	9,60	11,23	0,69	2,11	2,66	3,20	9,70	12,17	95	
2.5+3.5+3.5+4.2	1,75	2,45	2,45	2,94	4,51	9,60	11,23	0,74	2,09	2,62	3,50	9,60	12,00	95	
2.5+3.5+3.5+5.0	1,66	2,32	2,32	3,31	4,65	9,60	11,37	0,76	2,03	2,59	3,50	9,30	11,85	95	
2.5+3.5+4.2+4.2	1,67	2,33	2,80	2,80	4,66	9,60	11,24	0,77	2,06	2,59	3,60	9,50	11,85	95	
2.5+3.5+3.5+3.5	2,40	2,40	2,40	2,40	4,51	9,60	11,23	0,75	2,11	2,66	3,50	9,70	12,17	95	

Notes

- The total capacity of each connected indoor unit is up to 14.5 kW.
- The values mentioned in this document are for connecting with the following indoor unit types:
 ·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0, 7.1 kW class
 Wall-mounted ·CTXA-AS, CXTA-AT, CXTA-AW, CXTA-BB, CXTA-BS, CXTA-BT, CTXM-M, CTXM-N, CTXM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXM-M, FTXM-N, FTXM-R, FTXJ-AB, FTXJ-AS, FTXJ-AW series
- Heating capacity conditions
 Indoor temperature ·20°C DB
 Outdoor temperature ·7°C DB / ·6°C WB
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169.