

Heating · 230V 50Hz·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2MXM40M2V1B 2MXM40M3V1B 2MXM40M4V1B 2MXM40N2V1B 2MXM40N2V1B9 2MXM40A2V1B 2MXM40A2V1B9	1.5	2.00	-	1.00	2.00	3.30	0.26	0.68	1.04	1.43	3.66	5.69	79
	2.0	2.70	-	1.00	2.70	3.70	0.26	0.75	1.24	1.43	4.11	6.78	79
	2.5	3.40	-	1.00	3.40	4.10	0.26	1.02	1.48	1.43	5.59	8.09	79
	3.5	3.80	-	1.00	3.80	4.40	0.26	1.28	1.71	1.43	7.02	9.40	79
	1.5+1.5	1.75	1.75	1.20	3.50	4.30	0.24	0.80	0.99	1.31	4.43	5.45	79
	1.5+2.0	1.63	2.17	1.20	3.80	4.50	0.24	0.88	1.04	1.31	4.85	5.75	79
	1.5+2.5	1.58	2.63	1.20	4.20	4.60	0.24	1.00	1.10	1.31	5.53	6.06	79
	1.5+3.5	1.26	2.94	1.20	4.20	4.70	0.24	0.96	1.12	1.31	5.29	5.92	79
	2.0+2.0	2.10	2.10	1.20	4.20	4.60	0.22	0.98	1.08	1.21	5.41	5.93	79
	2.0+2.5	1.87	2.33	1.20	4.20	4.70	0.22	0.97	1.09	1.21	5.36	6.00	79
	2.0+3.5	1.53	2.67	1.20	4.20	4.80	0.22	0.95	1.09	1.21	5.25	6.00	79
	2.5+2.5	2.10	2.10	1.20	4.20	4.70	0.22	0.96	1.08	1.21	5.29	5.92	79
2.5+3.5	1.75	2.45	1.20	4.20	4.80	0.22	0.94	1.08	1.21	5.19	5.94	79	