

4MXM68A8

Cooling ·50Hz 230V·

①	②	Indoor air temperature [°C WB]											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0+2.5+2.5+3.5	22.0	8.68	1.96	9.06	2.01	9.42	2.05	9.61	2.07	10.18	2.14	10.56	2.18
	25.0	8.45	2.04	8.83	2.09	9.20	2.13	9.39	2.15	9.95	2.21	10.31	2.26
	32.0	7.91	2.24	8.29	2.29	8.67	2.33	8.86	2.35	9.42	2.41	9.80	2.46
	35.0	7.68	2.34	8.06	2.38	8.44	2.42	8.63	2.44	9.19	2.51	9.57	2.55
	40.0	7.30	2.50	7.68	2.54	8.06	2.58	8.25	2.60	8.81	2.67	9.19	2.71
	43.0	6.91	2.22	7.27	2.22	7.62	2.22	7.80	2.22	8.33	2.22	8.69	2.22
	46.0	5.71	1.71	6.01	1.71	6.30	1.71	6.45	1.71	6.89	1.71	7.18	1.71
	50.0	2.82	1.12	2.97	1.12	3.12	1.12	3.19	1.12	3.41	1.12	3.55	1.12
2.5+2.5+2.5+2.5	22.0	8.61	1.95	8.98	1.98	9.35	2.02	9.53	2.04	10.10	2.09	10.47	2.13
	25.0	8.38	2.01	8.75	2.05	9.13	2.08	9.31	2.11	9.87	2.17	10.23	2.21
	32.0	7.85	2.20	8.23	2.24	8.60	2.28	8.78	2.30	9.34	2.36	9.72	2.41
	35.0	7.62	2.29	8.00	2.33	8.37	2.37	8.56	2.39	9.12	2.45	9.49	2.50
	40.0	7.24	2.45	7.62	2.49	8.00	2.53	8.18	2.55	8.74	2.61	9.11	2.65
	43.0	6.76	2.51	7.11	2.51	7.46	2.51	7.63	2.51	8.15	2.51	8.32	2.51
	46.0	5.74	2.00	6.04	2.00	6.33	2.00	6.48	2.00	6.92	2.00	7.07	2.00
	50.0	2.78	1.22	2.93	1.22	3.07	1.22	3.14	1.22	3.36	1.22	3.43	1.22
2.5+2.5+2.5+3.5	22.0	8.95	2.13	9.34	2.17	9.72	2.21	9.91	2.23	10.50	2.30	10.89	2.35
	25.0	8.71	2.20	9.10	2.25	9.49	2.29	9.68	2.32	10.26	2.39	10.64	2.43
	32.0	8.16	2.42	8.55	2.46	8.94	2.51	9.13	2.53	9.71	2.60	10.10	2.65
	35.0	7.93	2.52	8.32	2.56	8.70	2.61	8.90	2.63	9.48	2.70	9.86	2.75
	40.0	7.53	2.69	7.92	2.74	8.31	2.78	8.51	2.81	9.09	2.87	9.47	2.92
	43.0	6.94	2.41	7.23	2.41	7.51	2.41	7.65	2.41	8.16	2.41	8.41	2.41
	46.0	6.01	1.90	6.26	1.90	6.50	1.90	6.62	1.90	7.06	1.90	7.28	1.90
	50.0	2.91	1.17	3.03	1.17	3.15	1.17	3.21	1.17	3.42	1.17	3.53	1.17

Symbols

TC: Total capacity [kW]

PI: Power input [kW]

① Indoor unit combinations

② Outdoor air temperature [°C DB]