

Cooling ·(50Hz 230V)·

Outdoor unit	Indoor unit	Cooling capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2AMXF40A2V1B	2,5	2,50	---	1,30	2,50	3,00	0,33	0,61	0,80	1,78	3,33	4,40	79
	3,5	3,50	---	1,30	3,50	4,00	0,33	1,04	1,35	1,78	5,71	7,38	79
	2.5+2.5	2,00	2,00	1,50	4,00	4,40	0,30	1,15	1,27	1,67	6,33	6,97	79
	2.5+3.5	1,67	2,33	1,50	4,00	4,60	0,30	1,13	1,30	1,67	6,24	7,18	79

Heating ·(50Hz 230V)·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2AMXF40A2V1B	2,5	3,40	---	1,00	3,40	4,10	0,26	1,02	1,50	1,43	5,59	8,09	79
	3,5	3,80	---	1,00	3,80	4,40	0,26	1,28	1,73	1,43	7,02	9,40	79
	2.5+2.5	2,10	2,10	1,30	4,20	4,70	0,24	1,03	1,16	1,31	5,70	6,38	79
	2.5+3.5	1,75	2,45	1,30	4,20	4,80	0,24	1,01	1,16	1,31	5,59	6,39	79

Notes

- 1) The total capacity of each connected indoor unit is up to ·6.0·kW.
- 2) The values above are for connecting with the following indoor unit types:
·2.5, 3.5· kW class
Wall-mounted ·ATXF-A· series
- 3) These indoor units can only be used in a multi-unit setup.
- 4) Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- 5) Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB