

Heating

·50· Hz

·230· V

①	②	Indoor air temperature [°C DB]											
		16°C		18°C		20°C		21°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2,5	-15,0	2,45	1,30	2,34	1,31	2,29	1,32	2,27	1,33	2,24	1,34	2,19	1,34
	-10,0	2,67	1,32	2,61	1,33	2,56	1,34	2,54	1,34	2,51	1,35	2,46	1,36
	-5,0	3,28	1,37	3,13	1,38	3,08	1,39	3,06	1,39	3,03	1,40	2,98	1,41
	0,0	3,70	1,42	3,65	1,43	3,60	1,44	3,57	1,44	3,55	1,45	3,50	1,46
	6,0	4,20	1,48	4,15	1,49	4,10	1,50	4,07	1,51	4,05	1,51	4,00	1,52
	10,0	4,54	1,52	4,49	1,53	4,43	1,54	4,41	1,55	4,38	1,55	4,33	1,56
	15,0	4,55	1,53	4,50	1,54	4,45	1,55	4,43	1,56	4,40	1,56	4,35	1,57
3,5	-15,0	2,64	1,52	2,58	1,53	2,53	1,54	2,50	1,55	2,47	1,56	2,42	1,57
	-10,0	2,93	1,53	2,87	1,54	2,81	1,55	2,78	1,56	2,75	1,57	2,69	1,58
	-5,0	3,43	1,54	3,37	1,56	3,31	1,57	3,28	1,58	3,25	1,59	3,19	1,61
	0,0	3,93	1,61	3,86	1,63	3,80	1,64	3,77	1,65	3,74	1,66	3,68	1,68
	6,0	4,52	1,70	4,46	1,71	4,40	1,73	4,37	1,74	4,34	1,75	4,28	1,76
	10,0	4,92	1,76	4,86	1,77	4,80	1,78	4,77	1,79	4,74	1,80	4,68	1,82
	15,0	4,94	1,77	4,88	1,78	4,82	1,79	4,79	1,80	4,76	1,81	4,70	1,82
2,5+2,5	-15,0	2,58	0,93	2,55	0,94	2,49	0,95	2,44	0,96	2,41	0,97	2,34	0,98
	-10,0	3,13	0,98	3,08	1,00	3,02	1,01	2,97	1,02	2,94	1,02	2,87	1,03
	-5,0	3,66	1,03	3,59	1,04	3,53	1,05	3,50	1,06	3,47	1,06	3,40	1,08
	0,0	4,19	1,08	4,12	1,09	4,06	1,10	4,03	1,11	4,00	1,11	3,93	1,12
	6,0	4,83	1,14	4,77	1,15	4,70	1,16	4,67	1,17	4,64	1,17	4,57	1,18
	10,0	5,19	1,18	5,15	1,19	5,12	1,20	5,09	1,20	5,06	1,21	4,99	1,22
	15,0	5,88	1,21	5,77	1,24	5,66	1,25	5,62	1,25	5,59	1,26	5,53	1,27
2,5+3,5	-15,0	2,70	0,95	2,69	0,95	2,62	0,97	2,59	0,97	2,56	0,98	2,49	0,99
	-10,0	3,28	0,99	3,22	1,00	3,15	1,01	3,12	1,02	3,09	1,02	3,02	1,03
	-5,0	3,81	1,04	3,75	1,05	3,68	1,06	3,65	1,06	3,62	1,07	3,55	1,08
	0,0	4,34	1,08	4,28	1,09	4,21	1,11	4,18	1,11	4,15	1,12	4,08	1,13
	6,0	4,98	1,14	4,91	1,15	4,80	1,16	4,75	1,17	4,74	1,17	4,72	1,18
	10,0	5,40	1,18	5,34	1,19	5,27	1,20	5,24	1,20	5,21	1,21	5,14	1,22
	15,0	6,09	1,21	5,87	1,24	5,81	1,25	5,77	1,25	5,74	1,26	5,68	1,27

Notes

1.The capacities are based on the following conditions:

Corresponding refrigerant piping length: ·5· m

Level difference: ·0·m

2.The bold cells indicate the standard conditions.

3.The values above are for connecting with the following indoor unit types:

·2.5, 3.5· kW class

Wall mounted type

ATXF-A

4.The heating capacity does not include the capacity drop that occurs during a frosting period and defrost operation.

Symbols

TC: Total capacity [kW]

PI: Power input [kW]

① Indoor unit combinations

② Outdoor air temperature [°C DB]