

Cooling ·(50Hz 230V)·

Outdoor unit	Indoor unit	Cooling capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2AMXF50A2V1B	2,5	2,50	---	1,40	2,50	3,10	0,31	0,67	0,92	1,53	3,27	4,50	89
	3,5	3,50	---	1,40	3,50	4,00	0,31	1,09	1,42	1,53	5,32	6,95	89
	2.5+2.5	2,50	2,50	1,80	5,00	5,30	0,54	1,49	1,66	2,63	7,30	7,74	89
	2.5+3.5	2,08	2,92	1,80	5,00	5,40	0,53	1,48	1,68	2,61	7,25	7,83	89
	3.5+3.5	2,50	2,50	1,80	5,00	5,40	0,53	1,48	1,68	2,61	7,23	7,81	89

Heating ·(50Hz 230V)·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2AMXF50A2V1B	2,5	3,40	---	1,10	3,40	4,10	0,25	0,99	1,31	1,23	4,81	6,54	89
	3,5	4,00	---	1,10	4,00	4,60	0,25	1,24	1,53	1,23	6,03	7,46	89
	2.5+2.5	2,80	2,80	1,20	5,60	5,80	0,33	1,51	1,57	1,59	7,38	7,65	89
	2.5+3.5	2,33	3,27	1,20	5,60	6,00	0,32	1,50	1,61	1,58	7,34	7,87	89
	3.5+3.5	2,80	2,80	1,30	5,60	6,10	0,35	1,49	1,63	1,70	7,30	7,96	89

Notes

- 1) The total capacity of each connected indoor unit is up to ·7.0·kW.
- 2) The values above are for connecting with the following indoor unit types:
·2.5, 3.5· kW class
Wall-mounted ·ATXF-A· series
- 3) These indoor units can only be used in a multi-unit setup.
- 4) Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- 5) Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB