

Unidad exterior	Suministro eléctrico			·RA· indoor units (·10·% safety factor) See note ·5·.		Other indoor units (·10·% safety factor)		Compresor		Motor del ventilador exterior	
	Nombre del modelo	Hz	Tensión	Rango de tensión	MCA	MFA	MCA	MFA	RHz	RLA	kW
2AMXF40B2V1B	50	220	Maximum ·50·Hz ·264·V Minimum ·50·Hz ·198·V	9.80	16	9.80	16	-	5.1	0.040	0.17
	50	230							5.3		
	50	240							5.6		
2AMXF50B2V1B	50	220	Maximum ·50·Hz ·264·V Minimum ·50·Hz ·198·V	12.83	16	12.83	16	-	5.9	0.042	0.18
	50	230							6.2		
	50	240							6.5		
2MXF40B2V1B	50	220	Maximum ·50·Hz ·264·V Minimum ·50·Hz ·198·V	9.80	16	9.80	16	-	5.1	0.040	0.17
	50	230							5.3		
	50	240							5.6		
2MXF50B2V1B	50	220	Maximum ·50·Hz ·264·V Minimum ·50·Hz ·198·V	12.83	16	12.83	16	-	5.9	0.042	0.18
	50	230							6.2		
	50	240							6.5		

Notes

- 1) The ·RLA· is based on the following conditions.
Outdoor temperature ·35·°C DB
Indoor temperature ·27·°C DB / ·19·°C WB
- 2) Select the wire size according to the MCA.
- 3) The maximum allowable voltage that is unbalanced between phases is ·2·%.
- 4) Use a circuit breaker instead of a fuse.
- 5) Only for wall-mounted ·FTXF· units

Symbols

- MCA: Minimum Circuit Ampere [A]
MFA: Maximum Fuse Ampere [A]
RLA: Rated load amps [A]
OFM: Outdoor fan motor
MSC: Maximum starting current
FLA: Full Load Ampere [A]
kW: Fan motor rated output [kW]