

2AMXF40B

Refrigeración 230V 50Hz

Unidad exterior	Unidad interior	Capacidad de refrigeración [kW]		Capacidad total [kW]			Consumo [kW]			Corriente total [A]			Factor de potencia [%]
		Ambiente A	Ambiente B	Mínimo	Nominal	Máxima	Mínimo	Nominal	Máxima	Mínimo	Nominal	Máxima	
2AMXF40B2V1B	2.5	2.50	-	1.30	2.50	3.00	0.33	0.59	0.77	1.61	2.87	3.76	89
	3.5	3.50	-	1.30	3.50	4.00	0.33	1.01	1.30	1.61	4.91	6.35	89
	2.5+2.5	2.50	2.50	1.50	4.00	4.50	0.30	0.95	1.24	1.47	4.66	6.07	89
	2.5+3.5	2.08	2.92	1.50	4.00	4.60	0.30	0.94	1.23	1.47	4.61	6.02	89

230V 50Hz calefacción

Unidad exterior	Unidad interior	Capacidad de calefacción [kW]		Capacidad total [kW]			Consumo [kW]			Corriente total [A]			Factor de potencia [%]
		Ambiente A	Ambiente B	Mínimo	Nominal	Máxima	Mínimo	Nominal	Máxima	Mínimo	Nominal	Máxima	
2AMXF40B2V1B	2.5	3.40	-	1.00	3.40	4.10	0.26	0.91	1.40	1.27	4.46	6.82	89
	3.5	4.00	-	1.00	3.80	4.40	0.26	1.15	1.61	1.27	5.60	7.87	89
	2.5+2.5	2.80	2.80	1.30	4.20	4.80	0.24	1.03	1.06	1.17	5.05	5.18	89
	2.5+3.5	2.33	3.27	1.30	4.20	4.80	0.24	0.88	1.06	1.17	4.29	5.18	89