

①	②	Indoor air temperature [°C WB]											
		14°C		16°C		18°C		19°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0+2.5+4.2	22.0	7.24	1.76	7.57	1.79	7.89	1.82	8.05	1.84	8.54	1.89	8.87	1.93
	25.0	7.04	1.82	7.37	1.85	7.69	1.89	7.86	1.91	8.35	1.96	8.67	1.99
	32.0	6.58	1.98	6.91	2.02	7.23	2.05	7.40	2.07	7.89	2.12	8.21	2.15
	35.0	6.39	2.06	6.71	2.09	7.04	2.13	7.20	2.14	7.69	2.19	8.01	2.23
	40.0	6.06	2.19	6.38	2.22	6.71	2.26	6.87	2.27	7.36	2.33	7.68	2.36
	43.0	5.86	2.27	6.19	2.31	6.51	2.34	6.67	2.36	7.16	2.41	7.49	2.45
	46.0	5.32	2.05	5.58	2.05	5.82	2.05	5.95	2.05	6.30	2.05	6.53	2.05
2.0+3.5+3.5	22.0	7.34	1.77	7.67	1.80	7.99	1.83	8.16	1.85	8.64	1.90	8.97	1.94
	25.0	7.14	1.83	7.47	1.86	7.80	1.90	7.96	1.92	8.45	1.97	8.77	2.00
	32.0	6.68	1.99	7.01	2.03	7.33	2.06	7.50	2.08	7.99	2.13	8.31	2.16
	35.0	6.49	2.07	6.81	2.10	7.14	2.14	7.30	2.15	7.79	2.20	8.11	2.24
	40.0	6.16	2.20	6.48	2.23	6.81	2.27	6.97	2.28	7.46	2.34	7.79	2.37
	43.0	5.96	2.28	6.28	2.32	6.61	2.35	6.77	2.37	7.26	2.42	7.59	2.46
	46.0	5.42	2.06	5.67	2.06	5.92	2.06	6.04	2.06	6.40	2.06	6.63	2.06
2.5+2.5+2.5	22.0	7.14	1.81	7.47	1.84	7.79	1.87	7.95	1.89	8.44	1.94	8.76	1.98
	25.0	6.94	1.87	7.27	1.90	7.59	1.94	7.76	1.96	8.24	2.01	8.57	2.04
	32.0	6.49	2.03	6.81	2.07	7.13	2.10	7.30	2.12	7.78	2.17	8.11	2.20
	35.0	6.29	2.11	6.61	2.14	6.94	2.18	7.10	2.19	7.59	2.24	7.91	2.28
	40.0	5.96	2.24	6.29	2.27	6.61	2.31	6.77	2.32	7.26	2.38	7.58	2.41
	43.0	5.76	2.32	6.09	2.36	6.41	2.39	6.58	2.41	7.06	2.46	7.39	2.50
	46.0	5.23	2.10	5.48	2.10	5.73	2.10	5.85	2.10	6.20	2.10	6.43	2.10
2.5+2.5+3.5	22.0	7.24	1.78	7.57	1.81	7.89	1.84	8.05	1.86	8.54	1.91	8.87	1.95
	25.0	7.04	1.84	7.37	1.87	7.69	1.91	7.86	1.93	8.35	1.98	8.67	2.01
	32.0	6.58	2.00	6.91	2.04	7.23	2.07	7.40	2.09	7.89	2.14	8.21	2.17
	35.0	6.39	2.08	6.71	2.11	7.04	2.15	7.20	2.16	7.69	2.21	8.01	2.25
	40.0	6.06	2.21	6.38	2.24	6.71	2.28	6.87	2.29	7.36	2.35	7.68	2.38
	43.0	5.86	2.29	6.19	2.33	6.51	2.36	6.67	2.39	7.16	2.43	7.49	2.47
	46.0	5.32	2.07	5.58	2.07	5.82	2.07	5.95	2.07	6.30	2.07	6.53	2.07

Notes

- The capacities are based on the following conditions:
Corresponding refrigerant piping length: ·5·m
Level difference: ·0·m
- The bold cells indicate the standard conditions.
- The values above are for connecting with the following indoor unit types:
· 2.0, 2.5, 3.5, 4.2 · kW class
Wall-mountend ·FTXM-M· series
- Editable data for this drawing are available in ·GDE· system.

Symbols

- TC: Total capacity [kW]
- PI: Power input [kW]
- ① Indoor unit combinations
- ② Outdoor air temperature [°C DB]