

①	②	Indoor air temperature [°C DB]											
		16°C		18°C		20°C		21°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
4.2+4.2	-15.0	4.08	1.90	3.98	1.92	3.88	1.94	3.83	1.95	3.78	1.96	3.68	1.99
	-10.0	4.89	2.00	4.79	2.02	4.69	2.04	4.64	2.05	4.59	2.06	4.49	2.08
	-5.0	5.71	2.09	5.61	2.12	5.51	2.14	5.46	2.15	5.41	2.16	5.31	2.18
	0.0	6.52	2.19	6.42	2.21	6.32	2.23	6.27	2.24	6.22	2.26	6.12	2.28
	6.0	7.50	2.31	7.40	2.33	7.30	2.35	7.25	2.36	7.20	2.37	7.10	2.39
	10.0	8.15	2.39	8.05	2.41	7.95	2.43	7.90	2.44	7.85	2.45	7.75	2.47
	15.0	8.97	2.48	8.87	2.50	8.77	2.52	8.72	2.53	8.67	2.55	8.57	2.57
1.5+1.5+1.5	-15.0	4.42	1.71	4.31	1.73	4.20	1.75	4.14	1.76	4.09	1.77	3.97	1.79
	-10.0	5.32	1.80	5.21	1.82	5.10	1.84	5.05	1.85	4.99	1.86	4.88	1.88
	-5.0	6.23	1.89	6.12	1.91	6.01	1.93	5.95	1.94	5.90	1.95	5.79	1.96
	0.0	7.13	1.98	7.02	1.99	6.91	2.01	6.86	2.02	6.80	2.03	6.69	2.05
	6.0	8.22	2.08	8.11	2.10	8.00	2.12	7.94	2.13	7.89	2.14	7.78	2.16
	10.0	8.95	2.15	8.84	2.17	8.72	2.19	8.67	2.20	8.61	2.21	8.50	2.23
	15.0	9.85	2.24	9.74	2.26	9.63	2.28	9.57	2.29	9.52	2.30	9.41	2.32
1.5+1.5+2.0	-15.0	4.42	1.69	4.31	1.71	4.20	1.73	4.14	1.74	4.09	1.75	3.97	1.77
	-10.0	5.32	1.78	5.21	1.80	5.10	1.82	5.05	1.83	4.99	1.84	4.88	1.86
	-5.0	6.23	1.87	6.12	1.89	6.01	1.91	5.95	1.92	5.90	1.93	5.79	1.94
	0.0	7.13	1.96	7.02	1.97	6.91	1.99	6.86	2.00	6.80	2.01	6.69	2.03
	6.0	8.22	2.06	8.11	2.08	8.00	2.10	7.94	2.11	7.89	2.12	7.78	2.14
	10.0	8.95	2.13	8.84	2.15	8.72	2.17	8.67	2.18	8.61	2.19	8.50	2.21
	15.0	9.85	2.22	9.74	2.24	9.63	2.26	9.57	2.27	9.52	2.28	9.41	2.30
1.5+1.5+2.5	-15.0	4.42	1.67	4.31	1.69	4.20	1.71	4.14	1.72	4.09	1.73	3.97	1.75
	-10.0	5.32	1.76	5.21	1.78	5.10	1.80	5.05	1.81	4.99	1.82	4.88	1.84
	-5.0	6.23	1.85	6.12	1.87	6.01	1.89	5.95	1.90	5.90	1.91	5.79	1.92
	0.0	7.13	1.94	7.02	1.95	6.91	1.97	6.86	1.98	6.80	1.99	6.69	2.01
	6.0	8.22	2.04	8.11	2.06	8.00	2.08	7.94	2.09	7.89	2.10	7.78	2.12
	10.0	8.95	2.11	8.84	2.13	8.72	2.15	8.67	2.16	8.61	2.17	8.50	2.19
	15.0	9.85	2.20	9.74	2.22	9.63	2.24	9.57	2.25	9.52	2.26	9.41	2.28
1.5+1.5+3.5	-15.0	4.50	1.72	4.39	1.74	4.28	1.76	4.23	1.77	4.17	1.78	4.06	1.80
	-10.0	5.41	1.81	5.30	1.83	5.19	1.85	5.14	1.86	5.08	1.87	4.97	1.89
	-5.0	6.32	1.90	6.21	1.92	6.10	1.94	6.04	1.95	5.99	1.96	5.88	1.97
	0.0	7.23	1.99	7.12	2.00	7.01	2.02	6.95	2.03	6.90	2.04	6.79	2.06
	6.0	8.32	2.09	8.21	2.11	8.10	2.13	8.04	2.14	7.99	2.15	7.88	2.17
	10.0	9.05	2.16	8.94	2.18	8.83	2.20	8.77	2.21	8.72	2.22	8.60	2.24
	15.0	9.96	2.25	9.85	2.27	9.74	2.29	9.68	2.30	9.63	2.31	9.51	2.33
1.5+1.5+4.2	-15.0	4.50	1.70	4.39	1.72	4.28	1.74	4.23	1.75	4.17	1.76	4.06	1.78
	-10.0	5.41	1.79	5.30	1.81	5.19	1.83	5.14	1.84	5.08	1.85	4.97	1.87
	-5.0	6.32	1.88	6.21	1.90	6.10	1.92	6.04	1.93	5.99	1.94	5.88	1.95
	0.0	7.23	1.97	7.12	1.98	7.01	2.00	6.95	2.01	6.90	2.02	6.79	2.04
	6.0	8.32	2.07	8.21	2.09	8.10	2.11	8.04	2.12	7.99	2.13	7.88	2.15
	10.0	9.05	2.14	8.94	2.16	8.83	2.18	8.77	2.19	8.72	2.20	8.60	2.22
	15.0	9.96	2.23	9.85	2.25	9.74	2.27	9.68	2.28	9.63	2.29	9.51	2.31

①	②	Indoor air temperature [°C DB]											
		16°C		18°C		20°C		21°C		22°C		24°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
1.5+1.5+5.0	-15.0	4.61	1.69	4.49	1.71	4.38	1.73	4.32	1.73	4.26	1.74	4.15	1.76
	-10.0	5.54	1.77	5.43	1.79	5.31	1.81	5.25	1.82	5.20	1.83	5.08	1.85
	-5.0	6.47	1.86	6.36	1.88	6.25	1.90	6.19	1.91	6.13	1.92	6.02	1.94
	0.0	7.41	1.95	7.29	1.97	7.18	1.99	7.12	2.00	7.07	2.00	6.95	2.02
	6.0	8.53	2.05	8.41	2.07	8.30	2.09	8.24	2.10	8.19	2.11	8.07	2.13
	10.0	9.28	2.12	9.16	2.14	9.05	2.16	8.99	2.17	8.93	2.18	8.82	2.20
	15.0	10.21	2.21	10.10	2.23	9.98	2.25	9.92	2.26	9.87	2.27	9.75	2.28
1.5+2.0+2.0	-15.0	4.42	1.73	4.31	1.75	4.20	1.77	4.14	1.78	4.09	1.79	3.97	1.81
	-10.0	5.32	1.82	5.21	1.84	5.10	1.86	5.05	1.87	4.99	1.88	4.88	1.90
	-5.0	6.23	1.91	6.12	1.93	6.01	1.95	5.95	1.96	5.90	1.97	5.79	1.98
	0.0	7.13	2.00	7.02	2.01	6.91	2.03	6.86	2.04	6.80	2.05	6.69	2.07
	6.0	8.22	2.10	8.11	2.12	8.00	2.14	7.94	2.15	7.89	2.16	7.78	2.18
	10.0	8.95	2.17	8.84	2.19	8.72	2.21	8.67	2.22	8.61	2.23	8.50	2.25
	15.0	9.85	2.26	9.74	2.28	9.63	2.30	9.57	2.31	9.52	2.32	9.41	2.34
1.5+2.0+2.5	-15.0	4.42	1.71	4.31	1.73	4.20	1.75	4.14	1.76	4.09	1.77	3.97	1.79
	-10.0	5.32	1.80	5.21	1.82	5.10	1.84	5.05	1.85	4.99	1.86	4.88	1.88
	-5.0	6.23	1.89	6.12	1.91	6.01	1.93	5.95	1.94	5.90	1.95	5.79	1.96
	0.0	7.13	1.98	7.02	1.99	6.91	2.01	6.86	2.02	6.80	2.03	6.69	2.05
	6.0	8.22	2.08	8.11	2.10	8.00	2.12	7.94	2.13	7.89	2.14	7.78	2.16
	10.0	8.95	2.15	8.84	2.17	8.72	2.19	8.67	2.20	8.61	2.21	8.50	2.23
	15.0	9.85	2.24	9.74	2.26	9.63	2.28	9.57	2.29	9.52	2.30	9.41	2.32
1.5+2.0+3.5	-15.0	4.50	1.75	4.39	1.77	4.28	1.79	4.23	1.80	4.17	1.81	4.06	1.83
	-10.0	5.41	1.84	5.30	1.86	5.19	1.88	5.14	1.89	5.08	1.90	4.97	1.92
	-5.0	6.32	1.93	6.21	1.95	6.10	1.97	6.04	1.98	5.99	1.99	5.88	2.00
	0.0	7.23	2.02	7.12	2.03	7.01	2.05	6.95	2.06	6.90	2.07	6.79	2.09
	6.0	8.32	2.12	8.21	2.14	8.10	2.16	8.04	2.17	7.99	2.18	7.88	2.20
	10.0	9.05	2.19	8.94	2.21	8.83	2.23	8.77	2.24	8.72	2.25	8.60	2.27
	15.0	9.96	2.28	9.85	2.30	9.74	2.32	9.68	2.33	9.63	2.34	9.51	2.36
1.5+2.0+4.2	-15.0	4.50	1.73	4.39	1.75	4.28	1.77	4.23	1.78	4.17	1.79	4.06	1.81
	-10.0	5.41	1.82	5.30	1.84	5.19	1.86	5.14	1.87	5.08	1.88	4.97	1.90
	-5.0	6.32	1.91	6.21	1.93	6.10	1.95	6.04	1.96	5.99	1.97	5.88	1.98
	0.0	7.23	2.00	7.12	2.01	7.01	2.03	6.95	2.04	6.90	2.05	6.79	2.07
	6.0	8.32	2.10	8.21	2.12	8.10	2.14	8.04	2.15	7.99	2.16	7.88	2.18
	10.0	9.05	2.17	8.94	2.19	8.83	2.21	8.77	2.22	8.72	2.23	8.60	2.25
	15.0	9.96	2.26	9.85	2.28	9.74	2.30	9.68	2.31	9.63	2.32	9.51	2.34
1.5+2.0+5.0	-15.0	4.61	1.67	4.49	1.69	4.38	1.71	4.32	1.71	4.26	1.72	4.15	1.74
	-10.0	5.54	1.75	5.43	1.77	5.31	1.79	5.25	1.80	5.20	1.81	5.08	1.83
	-5.0	6.47	1.84	6.36	1.86	6.25	1.88	6.19	1.89	6.13	1.90	6.02	1.92
	0.0	7.41	1.93	7.29	1.95	7.18	1.97	7.12	1.98	7.07	1.98	6.95	2.00
	6.0	8.53	2.03	8.41	2.05	8.30	2.07	8.24	2.08	8.19	2.09	8.07	2.11
	10.0	9.28	2.10	9.16	2.12	9.05	2.14	8.99	2.15	8.93	2.16	8.82	2.18
	15.0	10.21	2.19	10.10	2.21	9.98	2.23	9.92	2.24	9.87	2.25	9.75	2.26

Notes

- The capacities are based on the following conditions:
 Corresponding refrigerant piping length: · 5·m
 Level difference: · 0·m
- The bold cells indicate the standard conditios.
- The values above are for connecting with the following indoor unit types:
 · 1.5, 2.0, 2.5, 3.5, 4.2, 5.0 · kW class
 Wall-mounted · CTXM-M, FTXM-M series
- Editable data for this drawing are available in · GDE · system.

Symbols

- TC: Total capacity [kW]
 PI: Power input [kW]
 ① Indoor unit combinations
 ② Outdoor air temperature
 [° C WB]

3D105333