

Cooling ·(50Hz 230V)·

Outdoor unit	Indoor unit	Cooling capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Room ·D·	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
4MXM80N2V1B 4MXM80N2V1B9	1.5	1.80	---	---	---	1.73	1.80	2.89	0.42	0.52	1.00	1.91	2.38	4.57	95
	2.0	2.00	---	---	---	1.78	2.00	3.05	0.45	0.60	1.04	2.04	2.75	4.75	95
	2.5	2.50	---	---	---	1.85	2.50	3.59	0.48	0.78	1.31	2.18	3.57	5.99	95
	3.5	3.50	---	---	---	1.89	3.50	4.95	0.48	1.19	1.52	2.18	5.45	6.97	95
	4.2	---	4.20	---	---	1.94	4.20	5.02	0.49	1.43	1.53	2.22	6.55	7.01	95
	5.0	---	5.00	---	---	2.05	5.00	5.76	0.46	1.67	1.76	2.09	7.65	8.04	95
	6.0	---	6.00	---	---	2.15	6.00	6.73	0.46	2.01	2.36	2.09	9.20	10.79	95
	7.1	---	7.10	---	---	2.26	7.10	7.41	0.49	2.71	2.75	2.22	12.41	12.56	95
	1.5+1.5	1.50	1.50	---	---	1.87	3.00	4.11	0.42	0.47	0.97	1.94	2.16	4.44	95
	1.5+2.0	1.50	2.00	---	---	1.89	3.50	4.60	0.46	0.57	1.14	2.11	2.61	5.21	95
	1.5+2.5	1.50	2.50	---	---	1.95	4.00	5.07	0.42	0.69	1.23	1.94	3.16	5.62	95
	1.5+3.5	1.50	3.50	---	---	2.05	5.00	5.95	0.42	0.93	1.62	1.94	4.26	7.41	95
	1.5+4.2	1.50	4.20	---	---	2.12	5.70	6.51	0.46	1.14	1.87	2.11	5.22	8.55	95
	1.5+5.0	1.50	5.00	---	---	2.20	6.50	7.09	0.47	1.35	2.23	2.15	6.18	10.22	95
	1.5+6.0	1.48	5.92	---	---	2.32	7.40	7.74	0.51	1.64	2.38	2.32	7.51	10.88	95
	1.5+7.1	1.40	6.60	---	---	2.47	8.00	8.35	0.54	1.85	2.74	2.48	8.47	12.55	95
	2.0+2.0	2.00	2.00	---	---	1.95	4.00	5.41	0.46	0.68	1.49	2.11	3.12	6.80	95
	2.0+2.5	2.00	2.50	---	---	2.00	4.50	5.84	0.46	0.82	1.58	2.11	3.76	7.21	95
	2.0+3.5	2.00	3.50	---	---	2.10	5.50	6.44	0.46	1.06	2.17	2.11	4.86	9.94	95
	2.0+4.2	2.00	4.20	---	---	2.17	6.20	6.91	0.46	1.27	2.28	2.11	5.82	10.43	95
	2.0+5.0	2.00	5.00	---	---	2.25	7.00	7.45	0.47	1.47	2.46	2.15	6.73	11.24	95
	2.0+6.0	1.85	5.55	---	---	2.39	7.40	8.06	0.51	1.61	2.55	2.32	7.37	11.69	95
	2.0+7.1	1.76	6.24	---	---	2.53	8.00	8.62	0.54	1.76	2.93	2.48	8.06	13.40	95
	2.5+2.5	2.50	2.50	---	---	2.05	5.00	6.24	0.42	0.92	2.17	1.94	4.22	9.94	95
	2.5+3.5	2.50	3.50	---	---	2.15	6.00	6.73	0.46	1.24	2.12	2.11	5.68	9.69	95
	2.5+4.2	2.50	4.20	---	---	2.22	6.70	7.25	0.46	1.39	2.34	2.11	6.37	10.71	95
	2.5+5.0	2.47	4.93	---	---	2.32	7.40	7.74	0.50	1.61	2.63	2.27	7.37	12.06	95
	2.5+6.0	2.35	5.65	---	---	2.46	8.00	8.32	0.54	1.76	2.73	2.48	8.06	12.50	95
	2.5+7.1	2.08	5.92	---	---	2.60	8.00	8.83	0.54	1.79	3.05	2.48	8.20	13.97	95
	3.5+3.5	3.50	3.50	---	---	2.25	7.00	7.45	0.46	1.47	2.56	2.11	6.73	11.73	95
	3.5+4.2	3.50	4.20	---	---	2.35	7.70	7.88	0.50	1.69	2.74	2.27	7.74	12.55	95
	3.5+5.0	3.29	4.71	---	---	2.46	8.00	8.32	0.53	1.75	3.00	2.44	8.01	13.73	95
	3.5+6.0	2.95	5.05	---	---	2.58	8.00	8.79	0.54	1.73	3.66	2.48	7.92	16.74	95
	3.5+7.1	2.64	5.36	---	---	2.74	8.00	8.48	0.58	1.87	2.80	2.65	8.56	12.83	95
	4.2+4.2	---	4.00	4.00	---	2.44	8.00	8.27	0.53	1.81	3.04	2.44	8.29	13.93	95
	4.2+5.0	---	3.65	4.35	---	2.54	8.00	8.65	0.53	1.77	3.20	2.44	8.11	14.62	95
	4.2+6.0	---	3.29	4.71	---	2.68	8.00	9.07	0.58	1.82	3.26	2.65	8.33	14.91	95
	4.2+7.1	---	2.97	5.03	---	2.83	8.00	9.34	0.62	1.87	3.40	2.82	8.56	15.56	95
	5.0+5.0	---	4.00	4.00	---	2.65	8.00	8.83	0.57	1.74	3.22	2.61	7.97	14.75	95
	5.0+6.0	---	3.64	4.36	---	2.79	8.00	9.32	0.62	1.72	3.28	2.82	7.88	15.03	95

Notes

1.The total capacity of each connected indoor unit is up to ·14.5·kW.

2.The values above are for connecting with the following indoor unit types:

·1.5,2.0,2.5,3.5,4.2,5.0,6.0,7.1· kW class

Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series

3.Cooling capacity conditions

Indoor temperature ·27·°C DB / ·19·°C WB

Outdoor temperature ·35·°C DB

4.For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.