

Cooling (50Hz 230V)

Outdoor unit	Indoor unit	Cooling capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Room ·D·	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
4MXM80N2V1B 4MXM80N2V1B9	2.0+2.0+3.5	1.97	1.97	3.45	---	2.32	7.40	7.76	0.51	1.51	2.38	2.32	6.92	10.88	95
	2.0+2.0+4.2	1.95	1.95	4.10	---	2.42	8.00	8.17	0.51	1.75	2.55	2.32	8.01	11.69	95
	2.0+2.0+5.0	1.78	1.78	4.44	---	2.52	8.00	8.57	0.54	1.72	2.82	2.48	7.88	12.91	95
	2.0+2.0+6.0	1.60	1.60	4.80	---	2.65	8.00	9.00	0.55	1.81	2.79	2.53	8.29	12.79	95
	2.0+2.0+7.1	1.44	1.44	5.12	---	2.80	8.00	9.36	0.59	1.83	3.07	2.69	8.38	14.05	95
	2.0+2.5+2.5	2.00	2.50	2.50	---	2.25	7.00	7.45	0.48	1.36	2.21	2.19	6.23	10.10	95
	2.0+2.5+3.5	1.85	2.31	3.24	---	2.39	7.40	8.06	0.51	1.50	2.55	2.32	6.87	11.69	95
	2.0+2.5+4.2	1.84	2.30	3.86	---	2.48	8.00	8.43	0.54	1.75	2.68	2.48	8.01	12.26	95
	2.0+2.5+5.0	1.68	2.11	4.21	---	2.58	8.00	8.79	0.54	1.72	2.95	2.48	7.88	13.48	95
	2.0+2.5+6.0	1.52	1.90	4.57	---	2.72	8.00	9.17	0.59	1.84	2.93	2.69	8.43	13.40	95
	2.0+2.5+7.1	1.38	1.72	4.90	---	2.87	8.00	9.49	0.62	1.83	3.14	2.82	8.38	14.38	95
	2.0+3.5+3.5	1.78	3.11	3.11	---	2.52	8.00	8.57	0.54	1.74	2.87	2.48	7.97	13.12	95
	2.0+3.5+4.2	1.65	2.89	3.46	---	2.61	8.00	8.87	0.58	1.79	3.00	2.65	8.20	13.73	95
	2.0+3.5+5.0	1.52	2.67	3.81	---	2.72	8.00	9.17	0.58	1.83	3.21	2.65	8.38	14.70	95
	2.0+3.5+6.0	1.39	2.43	4.17	---	2.86	8.00	9.47	0.62	1.83	3.13	2.82	8.38	14.34	95
	2.0+3.5+7.1	1.27	2.22	4.51	---	3.01	8.00	9.28	0.62	1.81	2.94	2.82	8.29	13.44	95
	2.0+4.2+4.2	1.54	3.23	3.23	---	2.71	8.00	9.17	0.58	1.80	3.26	2.65	8.24	14.91	95
	2.0+4.2+5.0	1.43	3.00	3.57	---	2.82	8.00	9.41	0.62	1.84	3.36	2.82	8.43	15.36	95
	2.0+4.2+6.0	1.31	2.75	3.93	---	2.95	8.00	9.64	0.62	1.81	3.20	2.82	8.29	14.66	95
	2.0+4.2+7.1	1.20	2.53	4.27	---	3.11	8.00	9.79	0.65	1.79	3.28	2.99	8.20	15.03	95
	2.0+5.0+5.0	1.33	3.33	3.33	---	2.93	8.00	9.58	0.62	1.74	3.38	2.82	7.97	15.48	95
	2.0+5.0+6.0	1.23	3.08	3.69	---	3.06	8.00	9.73	0.65	1.72	3.23	2.99	7.88	14.79	95
	2.0+5.0+7.1	1.13	2.84	4.03	---	3.22	8.00	9.79	0.65	1.70	3.23	2.99	7.79	14.79	95
	2.0+6.0+6.0	1.14	3.43	3.43	---	3.20	8.00	9.79	0.66	1.71	3.00	3.03	7.83	13.73	95
	2.5+2.5+2.5	2.47	2.47	2.47	---	2.32	7.40	7.76	0.51	1.50	2.38	2.32	6.87	10.88	95
	2.5+2.5+3.5	2.35	2.35	3.29	---	2.46	8.00	8.32	0.54	1.74	2.74	2.48	7.97	12.55	95
	2.5+2.5+4.2	2.17	2.17	3.65	---	2.54	8.00	8.66	0.54	1.73	2.93	2.48	7.92	13.40	95
	2.5+2.5+5.0	2.00	2.00	4.00	---	2.65	8.00	9.00	0.58	1.81	3.08	2.65	8.29	14.09	95
	2.5+2.5+6.0	1.82	1.82	4.36	---	2.79	8.00	9.33	0.59	1.83	3.07	2.69	8.38	14.05	95
	2.5+2.5+7.1	1.65	1.65	4.69	---	2.94	8.00	9.60	0.62	1.81	3.21	2.82	8.29	14.70	95
	2.5+3.5+3.5	2.11	2.95	2.95	---	2.58	8.00	8.51	0.54	1.73	2.68	2.48	7.92	12.26	95
	2.5+3.5+4.2	1.96	2.75	3.29	---	2.68	8.00	9.07	0.58	1.81	3.06	2.65	8.29	14.01	95
	2.5+3.5+5.0	1.82	2.55	3.64	---	2.79	8.00	9.33	0.62	1.81	3.28	2.82	8.29	15.03	95
	2.5+3.5+6.0	1.67	2.33	4.00	---	2.93	8.00	9.58	0.62	1.79	3.20	2.82	8.20	14.66	95
	2.5+3.5+7.1	1.53	2.14	4.34	---	3.08	8.00	9.28	0.65	1.77	2.94	2.99	8.11	13.44	95
	2.5+4.2+4.2	1.83	3.08	3.08	---	2.78	8.00	9.20	0.62	1.87	3.27	2.82	8.56	14.95	95
	2.5+4.2+5.0	1.71	2.87	3.42	---	2.89	8.00	9.54	0.62	1.82	3.43	2.82	8.33	15.68	95
	2.5+4.2+6.0	1.57	2.65	3.78	---	3.02	8.00	9.72	0.62	1.80	3.28	2.82	8.24	14.99	95
	2.5+4.2+7.1	1.45	2.43	4.12	---	3.17	8.00	9.82	0.65	1.78	3.36	2.99	8.15	15.36	95
	2.5+5.0+5.0	1.60	3.20	3.20	---	3.00	8.00	9.66	0.65	1.73	3.45	2.99	7.92	15.80	95

Notes

- The total capacity of each connected indoor unit is up to ·14.5· kW.
- The values above are for connecting with the following indoor unit types:
·2.0,2.5,3.5,4.2,5.0,6.0,7.1· kW class
Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series
- Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.