

4MXM80N9

Heating (50Hz 230V)

Outdoor unit	Indoor unit	Heating capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room -A-	Room -B-	Room -C-	Room -D-	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
4MXM80M2V1B 4MXM80N2V1B 4MXM80N2V1B9	5.0+7.1	3,97	5,63	---	---	3,93	9,60	11,14	0,66	2,33	2,57	3,01	10,67	11,76	95
	6.0+6.0	4,80	4,80	---	---	3,90	9,60	11,14	0,63	2,27	2,55	2,88	10,39	11,67	95
	6.0+7.1	4,40	5,20	---	---	4,20	9,60	11,16	0,67	2,26	2,54	3,05	10,35	11,62	95
	7.1+7.1	4,80	4,80	---	---	4,51	9,60	11,20	0,73	2,20	2,48	3,36	10,07	11,86	95
	1.5+1.5+1.5	1,83	1,83	1,83	---	1,80	5,50	9,95	0,40	1,14	1,27	1,85	5,22	10,39	95
	1.5+1.5+2.0	1,83	1,83	2,44	---	1,94	6,10	10,13	0,41	1,32	1,35	1,89	6,05	10,76	95
	1.5+1.5+2.5	1,83	1,83	3,05	---	2,09	6,70	10,21	0,43	1,49	1,38	1,98	6,82	10,89	95
	1.5+1.5+3.5	1,85	1,85	4,31	---	2,38	8,00	10,32	0,47	1,88	1,50	2,15	8,61	11,44	95
	1.5+1.5+4.2	1,81	1,81	5,08	---	2,58	8,70	10,32	0,49	2,15	1,50	2,24	9,84	11,44	95
	1.5+1.5+5.0	1,74	1,74	5,81	---	2,79	9,30	10,49	0,50	2,21	1,58	2,28	10,12	11,81	95
	1.5+1.5+6.0	1,58	1,58	6,33	---	3,07	9,50	11,14	0,51	2,20	1,50	2,32	10,07	11,95	95
	1.5+1.5+7.1	1,43	1,43	6,75	---	3,38	9,60	11,17	0,54	2,21	1,49	2,45	10,12	11,91	95
	1.5+2.0+2.0	1,83	2,44	2,44	---	2,09	6,70	10,29	0,43	1,49	1,42	1,98	6,82	11,08	95
	1.5+2.0+2.5	1,83	2,43	3,04	---	2,23	7,30	10,39	0,45	1,68	1,45	2,06	7,69	11,21	95
	1.5+2.0+3.5	1,82	2,43	4,25	---	2,52	8,50	10,48	0,49	2,06	1,59	2,24	9,43	11,85	95
	1.5+2.0+4.2	1,75	2,34	4,91	---	2,71	9,00	10,49	0,51	2,22	1,58	2,32	10,17	11,81	95
	1.5+2.0+5.0	1,69	2,26	5,65	---	2,94	9,60	10,91	0,52	2,34	1,65	2,37	10,71	12,13	95
	1.5+2.0+6.0	1,52	2,02	6,06	---	3,21	9,60	11,14	0,53	2,22	1,50	2,41	10,17	11,95	95
	1.5+2.0+7.1	1,36	1,81	6,43	---	3,52	9,60	11,17	0,56	2,21	1,49	2,58	10,12	11,91	95
	1.5+2.5+2.5	1,85	3,08	3,08	---	2,38	8,00	10,50	0,47	1,95	1,45	2,15	8,93	11,21	95
	1.5+2.5+3.5	1,80	3,00	4,20	---	2,66	9,00	10,61	0,51	2,22	1,58	2,32	10,17	11,81	95
	1.5+2.5+4.2	1,76	2,93	4,92	---	2,86	9,60	10,61	0,53	2,42	1,58	2,41	11,08	11,81	95
	1.5+2.5+5.0	1,60	2,67	5,33	---	3,07	9,60	11,03	0,54	2,34	1,65	2,45	10,71	12,13	95
	1.5+2.5+6.0	1,44	2,40	5,76	---	3,35	9,60	11,14	0,55	2,22	1,50	2,50	10,17	11,95	95
	1.5+2.5+7.1	1,30	2,16	6,14	---	3,65	9,60	11,17	0,58	2,21	1,49	2,67	10,12	11,91	95
	1.5+3.5+3.5	1,69	3,95	3,95	---	2,94	9,60	10,62	0,55	2,38	1,58	2,54	10,90	11,81	95
	1.5+3.5+4.2	1,57	3,65	4,38	---	3,13	9,60	10,77	0,57	2,38	1,61	2,62	10,90	12,48	95
	1.5+3.5+5.0	1,44	3,36	4,80	---	3,35	9,60	10,96	0,57	2,34	1,60	2,62	10,71	11,95	95
	1.5+3.5+6.0	1,31	3,05	5,24	---	3,62	9,60	11,15	0,58	2,22	1,50	2,67	10,17	11,95	95
	1.5+3.5+7.1	1,19	2,78	5,63	---	3,93	9,60	11,18	0,62	2,21	1,48	2,84	10,12	11,86	95
	1.5+4.2+4.2	1,45	4,07	4,07	---	3,33	9,60	10,78	0,59	2,38	1,61	2,71	10,90	12,48	95
	1.5+4.2+5.0	1,35	3,77	4,49	---	3,54	9,60	11,02	0,62	2,34	1,68	2,84	10,71	12,27	95
	1.5+4.2+6.0	1,23	3,45	4,92	---	3,81	9,60	11,27	0,60	2,22	1,80	2,75	10,17	11,91	95
	1.5+4.2+7.1	1,13	3,15	5,33	---	4,12	9,60	11,30	0,67	2,21	1,78	3,05	10,12	11,86	95
	1.5+5.0+5.0	1,25	4,17	4,17	---	3,76	9,60	11,17	0,62	2,25	1,83	2,84	10,30	12,08	95
	1.5+5.0+6.0	1,15	3,84	4,61	---	4,04	9,60	11,41	0,63	2,14	1,75	2,88	9,80	11,95	95
	1.5+5.0+7.1	1,06	3,53	5,01	---	4,35	9,60	11,44	0,67	2,13	1,73	3,05	9,75	11,91	95
	1.5+6.0+6.0	1,07	4,27	4,27	---	4,31	9,60	11,65	0,64	2,07	1,67	2,93	9,48	11,60	95
	2.0+2.0+2.0	2,50	2,50	2,50	---	2,23	7,50	10,47	0,45	1,73	1,49	2,06	7,92	11,40	95
	2.0+2.0+2.5	2,46	2,46	3,08	---	2,38	8,00	10,55	0,47	1,87	1,53	2,15	8,56	11,58	95

Notes

- The total capacity of each connected indoor unit is up to -14.5-kW.
- The values above are for connecting with the following indoor unit types:
-1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0, 7.1- kW class
Wall-mounted ·FTXM-M, FTXM-N, FTXM-R- series
- Heating capacity conditions
Indoor temperature -20°C DB
Outdoor temperature -7°C DB / -6°C WB
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see -3D106169-.