

Heating (50Hz 230V)

Outdoor unit	Indoor unit	Heating capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room -A-	Room -B-	Room -C-	Room -D-	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
4MXM80M2V1B 4MXM80N2V1B 4MXM80N2V1B9	2.0+2.0+3.5	2,40	2,40	4,20	---	2,66	9,60	10,66	0,51	2,21	2,66	2,32	10,12	12,17	95
	2.0+2.0+4.2	2,29	2,29	4,81	---	2,86	9,40	10,66	0,53	2,41	2,66	2,41	11,03	11,99	95
	2.0+2.0+5.0	2,13	2,13	5,33	---	3,07	9,60	10,90	0,54	2,38	2,73	2,45	10,90	12,49	95
	2.0+2.0+6.0	1,92	1,92	5,76	---	3,35	9,60	11,14	0,55	2,26	2,50	2,50	10,35	11,95	95
	2.0+2.0+7.1	1,73	1,73	6,14	---	3,65	9,60	11,17	0,58	2,25	2,49	2,67	10,30	11,91	95
	2.0+2.5+2.5	2,43	3,04	3,04	---	2,52	8,50	10,57	0,49	2,10	2,62	2,24	9,62	11,99	95
	2.0+2.5+3.5	2,33	2,91	4,07	---	2,79	9,30	10,66	0,53	2,39	2,66	2,41	10,94	12,17	95
	2.0+2.5+4.2	2,21	2,76	4,63	---	2,99	9,60	10,67	0,55	2,50	2,64	2,54	11,45	12,08	95
	2.0+2.5+5.0	2,02	2,53	5,05	---	3,21	9,60	11,09	0,55	2,34	2,76	2,54	10,71	12,63	95
	2.0+2.5+6.0	1,83	2,29	5,49	---	3,49	9,60	11,14	0,56	2,22	2,50	2,58	10,17	11,95	95
	2.0+2.5+7.1	1,66	2,07	5,88	---	3,79	9,60	11,17	0,60	2,21	2,49	2,75	10,12	11,91	95
	2.0+3.5+3.5	2,13	3,73	3,73	---	3,07	9,60	10,76	0,55	2,38	2,61	2,54	10,90	12,48	95
	2.0+3.5+4.2	1,98	3,46	4,16	---	3,26	9,60	10,77	0,59	2,38	2,61	2,71	10,90	12,48	95
	2.0+3.5+5.0	1,83	3,20	4,57	---	3,49	9,60	11,14	0,59	2,34	2,83	2,71	10,71	12,95	95
	2.0+3.5+6.0	1,67	2,92	5,01	---	3,76	9,60	11,15	0,60	2,22	2,50	2,75	10,17	11,95	95
	2.0+3.5+7.1	1,52	2,67	5,41	---	4,07	9,60	11,18	0,65	2,21	2,48	2,97	10,12	11,86	95
	2.0+4.2+4.2	1,85	3,88	3,88	---	3,46	9,60	10,78	0,61	2,38	2,61	2,80	10,90	12,48	95
	2.0+4.2+5.0	1,71	3,60	4,29	---	3,68	9,60	10,91	0,64	2,34	2,57	2,93	10,71	12,26	95
	2.0+4.2+6.0	1,57	3,30	4,72	---	3,96	9,60	11,15	0,63	2,22	2,49	2,88	10,17	11,91	95
	2.0+4.2+7.1	1,44	3,03	5,12	---	4,26	9,60	11,19	0,69	2,21	2,48	3,14	10,12	11,86	95
	2.0+5.0+5.0	1,60	4,00	4,00	---	3,90	9,60	11,04	0,64	2,25	2,53	2,93	10,30	12,08	95
	2.0+5.0+6.0	1,48	3,69	4,43	---	4,17	9,60	11,28	0,65	2,14	2,50	2,97	9,80	11,95	95
	2.0+5.0+7.1	1,36	3,40	4,83	---	4,48	9,60	11,32	0,70	2,13	2,49	3,18	9,75	11,91	95
	2.0+6.0+6.0	1,37	4,11	4,11	---	4,45	9,60	11,52	0,66	2,07	2,43	3,01	9,48	11,60	95
	2.5+2.5+2.5	3,20	3,20	3,20	---	2,66	9,60	10,70	0,51	2,49	2,65	2,32	11,40	12,13	95
	2.5+2.5+3.5	2,82	2,82	3,95	---	2,94	9,60	10,90	0,55	2,46	2,73	2,54	11,26	12,49	95
	2.5+2.5+4.2	2,61	2,61	4,38	---	3,13	9,60	11,02	0,57	2,44	2,81	2,62	11,17	13,40	95
	2.5+2.5+5.0	2,40	2,40	4,80	---	3,35	9,60	11,10	0,57	2,35	2,79	2,62	10,76	12,77	95
	2.5+2.5+6.0	2,18	2,18	5,24	---	3,62	9,60	11,14	0,58	2,26	2,50	2,67	10,35	11,95	95
	2.5+2.5+7.1	1,98	1,98	5,63	---	3,93	9,60	11,17	0,62	2,26	2,49	2,84	10,35	11,91	95
	2.5+3.5+3.5	2,53	3,54	3,54	---	3,21	9,60	11,03	0,57	2,41	2,73	2,62	11,03	12,49	95
	2.5+3.5+4.2	2,35	3,29	3,95	---	3,41	9,60	11,04	0,61	2,39	2,72	2,80	10,94	12,45	95
	2.5+3.5+5.0	2,18	3,05	4,36	---	3,62	9,60	11,10	0,62	2,30	2,75	2,84	10,53	12,59	95
	2.5+3.5+6.0	2,00	2,80	4,80	---	3,90	9,60	11,15	0,63	2,25	2,50	2,88	10,30	11,95	95
	2.5+3.5+7.1	1,83	2,56	5,20	---	4,20	9,60	11,18	0,67	2,21	2,48	3,05	10,12	11,86	95
	2.5+4.2+4.2	2,20	3,70	3,70	---	3,60	9,60	11,04	0,64	2,37	2,72	2,93	10,85	12,45	95
	2.5+4.2+5.0	2,05	3,45	4,10	---	3,81	9,60	11,10	0,66	2,28	2,57	3,01	10,44	11,76	95
	2.5+4.2+6.0	1,89	3,17	4,54	---	4,09	9,60	11,15	0,65	2,24	2,49	2,97	10,26	11,91	95
	2.5+4.2+7.1	1,74	2,92	4,94	---	4,40	9,60	11,19	0,71	2,20	2,48	3,27	10,07	11,86	95
	2.5+5.0+5.0	1,92	3,84	3,84	---	4,04	9,60	11,04	0,67	2,26	2,53	3,05	10,35	12,08	95

Notes

- The total capacity of each connected indoor unit is up to -14.5-kW.
- The values above are for connecting with the following indoor unit types:
-2.0, 2.5, 3.5, 4.2, 5.0, 6.0, 7.1- kW class
Wall-mounted -FTXM-M, FTXM-N, FTXM-R- series
- Heating capacity conditions
Indoor temperature -20-°C DB
Outdoor temperature -7-°C DB / -6-°C WB
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see -3D106169-.