

Cooling ·(50Hz 230V)·

Outdoor unit	Indoor unit	Cooling capacity [kW]					Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Room ·D·	Room ·E·	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
5MXM90N2V1B 5MXM90N2V1B9	1.5+1.5+1.5	1,50	1,50	1,50	---	---	2,14	4,50	5,51	0,43	0,83	1,24	1,98	3,80	5,66	95
	1.5+1.5+2.0	1,50	1,50	2,00	---	---	2,20	5,00	5,94	0,43	0,96	1,40	1,98	4,40	6,39	95
	1.5+1.5+2.5	1,50	1,50	2,50	---	---	2,25	5,50	6,34	0,43	1,09	1,57	1,98	4,99	7,17	95
	1.5+1.5+3.5	1,50	1,50	3,50	---	---	2,36	6,50	7,11	0,46	1,38	1,93	2,11	6,32	8,84	95
	1.5+1.5+4.2	1,50	1,50	4,20	---	---	2,44	7,20	7,60	0,46	1,61	2,18	2,11	7,37	9,98	95
	1.5+1.5+5.0	1,41	1,41	4,69	---	---	2,55	7,50	8,12	0,50	1,75	2,41	2,27	8,01	11,04	95
	1.5+1.5+6.0	1,33	1,33	5,33	---	---	2,70	8,00	8,70	0,53	1,96	2,51	2,44	8,98	11,49	95
	1.5+1.5+7.1	1,26	1,26	5,98	---	---	2,86	8,50	9,25	0,56	2,20	2,87	2,57	10,07	13,12	95
	1.5+2.0+2.0	1,50	2,00	2,00	---	---	2,25	5,50	6,34	0,46	1,09	1,57	2,11	4,99	7,17	95
	1.5+2.0+2.5	1,50	2,00	2,50	---	---	2,31	6,00	6,73	0,43	1,23	1,74	1,98	5,63	7,98	95
	1.5+2.0+3.5	1,50	2,00	3,50	---	---	2,42	7,00	7,46	0,46	1,52	2,14	2,11	6,96	9,78	95
	1.5+2.0+4.2	1,50	2,00	4,20	---	---	2,51	7,70	7,93	0,50	1,83	2,39	2,27	8,38	10,96	95
	1.5+2.0+5.0	1,41	1,88	4,71	---	---	2,63	8,00	8,42	0,50	1,95	2,57	2,27	8,93	11,77	95
	1.5+2.0+6.0	1,26	1,68	5,05	---	---	2,77	8,00	8,96	0,53	1,94	2,68	2,44	8,88	12,26	95
	1.5+2.0+7.1	1,27	1,70	6,03	---	---	2,93	9,00	9,30	0,56	2,39	2,87	2,57	10,94	13,12	95
	1.5+2.5+2.5	1,50	2,50	2,50	---	---	2,36	6,50	7,11	0,46	1,39	1,93	2,11	6,37	8,84	95
	1.5+2.5+3.5	1,50	2,50	3,50	---	---	2,48	7,50	7,79	0,50	1,72	2,29	2,27	7,88	10,47	95
	1.5+2.5+4.2	1,46	2,44	4,10	---	---	2,58	8,00	8,24	0,50	1,99	2,56	2,27	9,11	11,73	95
	1.5+2.5+5.0	1,33	2,22	4,44	---	---	2,70	8,00	8,70	0,52	1,95	2,75	2,40	8,93	12,59	95
	1.5+2.5+6.0	1,28	2,13	5,10	---	---	2,85	8,50	9,21	0,53	2,20	2,87	2,44	10,07	13,12	95
	1.5+2.5+7.1	1,22	2,03	5,76	---	---	3,01	9,00	9,49	0,56	2,39	2,99	2,57	10,94	13,69	95
	1.5+3.5+3.5	1,41	3,29	3,29	---	---	2,63	8,00	8,42	0,52	2,00	2,67	2,40	9,16	12,22	95
	1.5+3.5+4.2	1,30	3,04	3,65	---	---	2,73	8,00	8,65	0,52	1,99	2,79	2,40	9,11	12,75	95
	1.5+3.5+5.0	1,28	2,98	4,25	---	---	2,85	8,50	8,83	0,56	2,20	2,81	2,57	10,07	12,87	95
	1.5+3.5+6.0	1,23	2,86	4,91	---	---	2,99	9,00	9,29	0,56	2,39	2,87	2,57	10,94	13,12	95
	1.5+3.5+7.1	1,12	2,60	5,28	---	---	3,16	9,00	9,50	0,59	2,36	2,99	2,69	10,81	13,69	95
	1.5+4.2+4.2	1,36	---	3,82	3,82	---	2,83	9,00	9,17	0,55	2,23	2,79	2,53	10,21	12,75	95
	1.5+4.2+5.0	1,26	---	3,53	4,21	---	2,95	9,00	9,19	0,56	2,18	2,81	2,57	9,98	12,87	95
	1.5+4.2+6.0	1,15	---	3,23	4,62	---	3,10	9,00	9,49	0,59	2,15	2,99	2,69	9,84	13,69	95
	1.5+4.2+7.1	1,05	---	2,95	4,99	---	3,26	9,00	9,51	0,63	2,13	2,99	2,86	9,75	13,69	95
	1.5+5.0+5.0	1,17	---	3,91	3,91	---	3,07	9,00	9,20	0,59	2,04	2,95	2,69	9,34	13,52	95
	1.5+5.0+6.0	1,08	---	3,60	4,32	---	3,21	9,00	9,66	0,59	2,03	3,02	2,69	9,30	13,81	95
	1.5+5.0+7.1	0,99	---	3,31	4,70	---	3,38	9,00	9,68	0,63	2,01	3,02	2,86	9,20	13,81	95
	1.5+6.0+6.0	1,00	---	4,00	4,00	---	3,36	9,00	10,13	0,63	2,02	3,08	2,86	9,25	14,09	95
	1.5+6.0+7.1	1,19	---	3,58	4,23	---	3,51	9,00	10,15	0,65	2,00	3,08	2,99	9,16	14,09	95
	2.0+2.0+2.0	2,00	2,00	2,00	---	---	2,31	6,00	6,76	0,46	1,23	1,74	2,11	5,63	7,98	95
	2.0+2.0+2.5	2,00	2,00	2,50	---	---	2,36	6,50	7,11	0,46	1,39	1,93	2,11	6,37	8,84	95
	2.0+2.0+3.5	2,00	2,00	3,50	---	---	2,48	7,50	7,79	0,50	1,72	2,29	2,27	7,88	10,47	95
	2.0+2.0+4.2	2,00	2,00	4,20	---	---	2,58	8,20	8,24	0,50	2,04	2,56	2,27	9,34	11,73	95
	2.0+2.0+5.0	1,78	1,78	4,44	---	---	2,70	8,00	8,70	0,52	1,95	2,75	2,40	8,93	12,59	95
	2.0+2.0+6.0	1,70	1,70	5,10	---	---	2,85	8,50	9,21	0,53	2,20	2,87	2,44	10,07	13,12	95
	2.0+2.0+7.1	1,62	1,62	5,76	---	---	3,01	9,00	9,49	0,56	2,36	2,99	2,57	10,81	13,69	95
	2.0+2.5+2.5	2,00	2,50	2,50	---	---	2,42	7,00	7,46	0,46	1,52	2,14	2,11	6,96	9,78	95
	2.0+2.5+3.5	1,88	2,34	3,28	---	---	2,55	7,50	8,12	0,50	1,72	2,50	2,27	7,88	11,45	95

Notes

- 1.The total capacity of each connected indoor unit is up to ·14.6·kW.
- 2.The values above are for connecting with the following indoor unit types:
·1.5,2.0,2.5,3.5,4.2,5.0,6.0,7.1· kW class
Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series
- 3.These indoor units can only be used in a multi-unit setup.
- 4.Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB

Outdoor temperature ·35·°C DB