

ARXB25-35C

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	1	2	3	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
ATX25J3V1B	ARX25K2V1B	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	48	3,2	0,033	0,17	0,016	0,12
ATX35J3V1B	ARX35K2V1B	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	70	4,7	0,033	0,17	0,016	0,12

Notes

- 1

The RLA is based on the following conditions.
Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB
- 2

Select the wire size according to the MCA.
- 3

The maximum allowable voltage that is unbalanced between phases is -2%.
- 4

Use a circuit breaker instead of a fuse.

Symbols		
1	Hz	OFM Outdoor fan motor
2	Voltage	IFM Indoor fan motor
3	Voltage range	FLA Full Load Ampere (A)
MCA	Minimum Circuit Ampere (A)	kW Fan motor rated output [kW]
MFA	Maximum Fuse Ampere (A)	RHz Rated operating frequency [Hz]
RLA	Rated load amps [A]	