

ATXB25-35C_ARXB25-35C

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	1	2	3	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
FTXB25B1V1	RXB25B6V19	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	68	3,00	0,033	0,17	0,016	0,12
FTXB35B1V1	RXB35B6V19	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	71	3,92	0,033	0,17	0,016	0,12
ATXN25NV1B7	ARXN25N6V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	8,44	16	48	3,30	0,041	0,36	0,018	0,19
ATXN35NV1B7	ARXN35N6V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	9,69	16	70	5,20	0,041	0,34	0,018	0,21
ATXN25NV1B9	ARXN25N6V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	8,44	16	48	3,30	0,041	0,36	0,018	0,19
ATXN35NV1B9	ARXN35N6V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	9,69	16	70	5,20	0,041	0,34	0,018	0,21
FTXB20C2V1B	RXB20C5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	36	2,20	0,033	0,17	0,016	0,12
FTXB25C2V1B	RXB25C5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	48	3,20	0,033	0,17	0,016	0,12
FTXB35C2V1B	RXB35C5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	70	4,70	0,033	0,17	0,016	0,12
ATX20J3V1B	ARX20K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	36	2,20	0,033	0,17	0,016	0,12
ATX25J3V1B	ARX25K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	48	3,20	0,033	0,17	0,016	0,12
ATX35J3V1B	ARX35K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	70	4,70	0,033	0,17	0,016	0,12
ATXB25C2V1B	ARXB25C5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	48	3,20	0,033	0,17	0,016	0,12
ATXB35C2V1B	ARXB35C5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	13,71	16	70	4,70	0,033	0,17	0,016	0,12
FTX20K2V1B	RX20K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	36	2,20	0,033	0,17	0,022	0,20
FTX25K2V1B	RX25K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	48	3,20	0,033	0,17	0,022	0,20
FTX35K2V1B	RX35K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	70	4,70	0,033	0,17	0,028	0,23
ATX20K2V1B	ARX20K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	36	2,20	0,033	0,17	0,022	0,20
ATX25K2V1B	ARX25K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	48	3,20	0,033	0,17	0,022	0,20
ATX35K2V1B	ARX35K5V1B9	50 50 50	220 230 240	MAX. 50Hz 264V MIN. 50Hz 198V	14,00	16	70	4,70	0,033	0,17	0,028	0,23

Symbols

- 1 Hz
 2 Voltage
 3 Voltage range
 MCA Minimum Circuit Ampere (A)
 MFA Maximum Fuse Ampere (A)
 RLA Rated load amps [A]

- OFM Outdoor fan motor
 IFM Indoor fan motor
 FLA Full Load Ampere (A)
 kW Fan motor rated output [kW]
 RHz Rated operating frequency [Hz]

Notes

- 1 The RLA is based on the following conditions.
 Indoor temperature :27.°C DB / -19.°C WB
 Outdoor temperature :35.°C DB
 2 Select the wire size according to the MC A.
 3 The maximum allowable voltage that is unbalanced between phases is -2.%.
 4 Use a circuit breaker instead of a fuse.

3D106480A