

**ARXL-M**

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	A	B	C	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
ATXL35J2V1B	ARXL35M2V1B	50	220	MAX. 50 Hz 264V	13.5	20	60	6.4	0.05	0.23	0.016	0.12
		50	230					6.2				
		50	240	MIN. 50Hz 198V				6.0				
ATXL25J2V1B	ARXL25M2V1B	50	220	MAX. 50 Hz 264V	13.5	20	37	4.0	0.05	0.23	0.016	0.12
		50	230					3.8				
		50	240	MIN. 50Hz 198V				3.6				

**Notes**

- 1 The RLA is based on the following conditions.  
Indoor temperature 27°C DB / 19°C WB  
Outdoor temperature 35°C DB
- 2 The maximum allowable voltage that is unbalanced between phases is 2%.
- 3 Select the wire size according to the MCA.
- 4 Use a circuit breaker instead of a fuse.

**Symbols**

- |     |                            |     |                                |
|-----|----------------------------|-----|--------------------------------|
| A   | Hz                         | OFM | Outdoor fan motor              |
| B   | Voltage                    | IFM | Indoor fan motor               |
| C   | Voltage range              | FLA | Full Load Ampere (A)           |
| MCA | Minimum Circuit Ampere (A) | kW  | Fan motor rated output [kW]    |
| MFA | Maximum Fuse Ampere (A)    | RHz | Rated operating frequency [Hz] |
| RLA | Rated load amps [A]        |     |                                |