

Unit combination restrictions		Power supply						OFM		IFM	
Outdoor unit	Indoor unit	Hz	Voltage	Voltage range	MCA	MFA	RLA	kW	FLA	kW	FLA
RXP50N5V1B9	FTXP50N2V1B	50	220	MAX. 50Hz 264V MIN. 50Hz 198V	15.13	16	6.5	0.066	0.83	0.045	0.43
		50	230				6.3				
		50	240				6.1				
RXP60N5V1B9	FTXP60N2V1B	50	220	MAX. 50Hz 264V MIN. 50Hz 198V	15.16	16	8.1	0.066	0.83	0.049	0.46
		50	230				8.0				
		50	240				7.9				
RXP71N5V1B9	FTXP71N2V1B	50	220	MAX. 50Hz 264V MIN. 50Hz 198V	15.16	16	11.9	0.066	0.83	0.049	0.46
		50	230				11.8				
		50	240				11.7				

Symbols

- MCA: Minimum Circuit Amperes [A]
MFA: Maximum Fuse Amperes [A]
COMP: Compressor
RHZ: Rated operating frequency [Hz]
RLA: Rated Load Amperes [A]
OFM: Outdoor fan motor
IFM: Indoor fan motor
kW: Fan motor rated output [kW]
FLA: Full Load Amperes [A]
MAX.: Maximum
MIN.: Minimum

Notes

- 1) The ·RLA· is based on the following conditions.
Outdoor temperature ·35·°C DB
Indoor temperature ·27·°C DB / ·19·°C WB
2) Select the wire size according to the MCA.
3) The maximum allowable voltage that is unbalanced between phases is ·2·%.
4) Use a circuit breaker instead of a fuse.