2MKS40G

★ Cooling (50Hz 230V)

Combination (Capacity)	outdoor air temp.	Indoor air temp.: °CWB											
		14.0°C		16.0°C		18.0°C		19.0°C		22.0°C		24.0°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0	10.0	2.68	0.44	2.79	0.45	2.90	0.46	2.96	0.46	3.12	0.48	3.24	0.49
	12.0	2.64	0.45	2.75	0.46	2.86	0.47	2.91	0.47	3.08	0.49	3.19	0.50
	15.0	2.57	0.46	2.68	0.47	2.79	0.48	2.85	0.49	3.01	0.50	3.12	0.51
	18.0	2.50	0.48	2.61	0.49	2.72	0.50	2.78	0.50	2.95	0.52	3.06	0.53
	20.0	2.46	0.49	2.57	0.50	2.68	0.51	2.74	0.51	2.90	0.53	3.01	0.54
	22.0	2.41	0.50	2.52	0.51	2.64	0.52	2.69	0.53	2.86	0.54	2.97	0.55
	25.0	2.35	0.52	2.46	0.53	2.57	0.54	2.62	0.54	2.79	0.56	2.90	0.57
	28.0	2.28	0.54	2.39	0.55	2.50	0.56	2.56	0.56	2.72	0.58	2.83	0.59
	32.0	2.19	0.57	2.30	0.57	2.41	0.58	2.47	0.59	2.63	0.60	2.74	0.61
	35.0	2.12	0.59	2.23	0.60	2.34	0.61	**2.40**	**0.61**	2.57	0.63	2.68	0.64
	40.0	2.01	0.62	2.12	0.63	2.23	0.64	2.29	0.65	2.45	0.66	2.56	0.67
	43.0	1.94	0.65	2.06	0.66	2.17	0.67	2.22	0.67	2.39	0.69	2.50	0.70
	46.0	1.88	0.67	1.99	0.68	2.10	0.69	2.15	0.70	2.32	0.71	2.43	0.72
2.5	10.0	2.89	0.51	3.49	0.63	3.63	0.65	3.70	0.65	3.91	0.67	4.04	0.69
	12.0	2.89	0.54	3.44	0.65	3.57	0.66	3.64	0.67	3.85	0.69	3.99	0.70
	15.0	2.89	0.57	3.35	0.67	3.49	0.68	3.56	0.69	3.77	0.71	3.90	0.72
	18.0	2.89	0.61	3.27	0.69	3.41	0.70	3.47	0.71	3.68	0.73	3.82	0.74
	20.0	2.89	0.64	3.21	0.70	3.35	0.72	3.42	0.72	3.63	0.75	3.76	0.76
	22.0	2.89	0.67	3.16	0.72	3.29	0.73	3.36	0.74	3.57	0.76	3.71	0.78
	25.0	2.89	0.72	3.07	0.75	3.21	0.76	3.28	0.77	3.49	0.79	3.62	0.80
	28.0	2.85	0.76	2.99	0.77	3.13	0.79	3.20	0.79	3.40	0.81	3.54	0.83
	32.0	2.74	0.80	2.88	0.81	3.01	0.82	3.08	0.83	3.29	0.85	3.43	0.87
	35.0	2.65	0.83	2.79	0.84	2.93	0.85	**3.00**	**0.86**	3.241	0.88	3.35	0.90
	40.0	2.51	0.88	2.65	0.89	2.79	0.91	2.86	0.91	3.07	0.93	3.21	0.95
	43.0	2.43	0.91	2.57	0.93	2.71	0.94	2.78	0.95	2.98	0.97	3.12	0.98
	46.0	2.35	0.95	2.49	0.96	2.62	0.98	2.69	0.98	2.90	1.00	3.04	1.02
3.5	10.0	3.07	0.62	3.78	0.79	4.53	0.98	4.93	1.08	5.21	1.12	5.39	1.14
	12.0	3.07	0.65	3.78	0.82	4.53	1.02	4.86	1.11	5.13	1.14	5.32	1.17
	15.0	3.07	0.69	3.78	0.87	4.53	1.09	4.75	1.14	5.02	1.18	5.21	1.20
	18.0	3.07	0.73	3.78	0.93	4.53	1.16	4.63	1.18	4.91	1.21	5.09	1.24
	20.0	3.07	0.77	3.78	0.97	4.47	1.19	4.56	1.21	4.84	1.24	5.02	1.26
	22.0	3.07	0.80	3.78	1.02	4.39	1.22	4.48	1.23	4.76	1.27	4.94	1.29
	25.0	3.07	0.86	3.78	1.10	4.28	1.26	4.37	1.27	4.65	1.31	4.83	1.33
	28.0	3.07	0.92	3.78	1.18	4.17	1.31	4.26	1.32	4.54	1.35	4.72	1.38
	32.0	3.07	1.02	3.78	1.31	4.02	1.37	4.11	1.38	4.39	1.42	4.57	1.44
	35.0	3.07	1.11	3.72	1.40	3.91	1.42	**4.00**	**1.43**	4.28	1.47	4.46	1.49
	40.0	3.07	1.27	3.54	1.49	3.72	1.51	3.81	1.52	4.09	1.55	4.27	1.58
	43.0	3.07	1.39	3.38	1.50	3.53	1.50	3.60	1.50	3.81	1.50	3.95	1.50
	46.0	2.80	1.30	2.93	1.30	3.06	1.30	3.12	1.30	3.31	1.30	3.43	1.30

Combination (Capacity)	outdoor air temp.	Indoor air temp.: °CWB											
		14.0°C		16.0°C		18.0°C		19.0°C		22.0°C		24.0°C	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
2.0+2.0	10.0	4.58	0.84	4.77	0.86	4.96	0.88	5.05	0.89	5.34	0.92	5.53	0.94
	12.0	4.51	0.86	4.69	0.88	4.88	0.90	4.98	0.91	5.26	0.93	5.45	0.95
	15.0	4.39	0.89	4.58	0.91	4.77	0.93	4.86	0.93	5.15	0.96	5.34	0.98
	18.0	4.28	0.92	4.47	0.94	4.65	0.96	4.75	0.97	5.03	0.99	5.22	1.01
	20.0	4.20	0.94	4.39	0.96	4.58	0.98	4.67	0.99	4.96	1.01	5.14	1.03
	22.0	4.12	0.96	4.31	0.98	4.50	1.00	4.60	1.01	4.88	1.04	5.07	1.06
	25.0	4.01	1.00	4.20	1.01	4.39	1.03	4.48	1.04	4.77	1.07	4.95	1.09
	28.0	3.90	1.03	4.08	1.05	4.27	1.07	4.37	1.08	4.65	1.11	4.84	1.13
	32.0	3.74	1.08	3.93	1.10	4.12	1.12	4.21	1.13	4.50	1.16	4.69	1.18
	35.0	3.63	1.12	3.82	1.14	4.01	1.16	**4.10**	**1.17**	4.38	1.20	4.57	1.22
	40.0	3.44	1.20	3.63	1.22	3.81	1.23	3.91	1.24	4.19	1.27	4.38	1.29
	43.0	3.32	1.24	3.51	1.26	3.70	1.28	3.79	1.29	4.08	1.32	4.27	1.34
	46.0	3.21	1.29	3.39	1.30	3.54	1.30	3.61	1.30	3.83	1.30	3.98	1.30
2.0+2.5	10.0	4.69	0.87	4.89	0.89	5.08	0.91	5.18	0.92	5.47	0.95	5.66	0.97
	12.0	4.62	0.89	4.81	5.00	0.93	5.10	0.94	5.39	0.97	5.58	0.99	15.0
	15.0	4.50	0.92	4.69	0.94	4.89	0.96	4.98	0.97	5.27	1.00	5.47	1.02
	18.0	4.38	0.95	4.57	0.97	4.77	0.99	4.86	1.00	5.16	1.03	5.35	1.05
	20.0	4.30	0.97	4.50	0.99	4.69	1.01	4.79	1.02	5.08	1.05	5.27	1.07
	22.0	4.22	0.99	4.42	1.01	4.61	1.03	4.71	1.04	5.00	1.07	5.19	1.09
	25.0	4.11	1.0	4.30	1.05	4.49	1.07	4.59	1.08	4.88	1.11	5.07	1.13
	28.0	3.99	1.07	4.18	1.09	4.38	1.11	4.47	1.12	4.76	1.15	4.96	1.16
	32.0	3.83	1.12	4.03	1.14	4.22	1.16	4.32	1.17	4.61	1.20	4.80	1.22
	35.0	3.72	1.16	3.91	1.18	4.10	1.20	**4.20**	**1.21**	4.49	1.24	4.68	1.26
	40.0	3.52	1.24	3.71	1.26	3.91	1.28	4.00	1.29	4.29	1.31	4.49	1.33
	43.0	3.40	1.28	3.60	1.30	3.79	1.32	3.89	1.33	4.18	1.36	4.37	1.38
	46.0	3.24	1.30	3.39	1.30	3.54	1.30	3.62	1.30	3.83	1.30	3.97	1.30
2.0+3.5	10.0	4.92	0.97	5.12	0.99	5.32	1.01	5.42	1.03	5.73	1.06	5.93	1.08
	12.0	4.84	0.99	5.04	1.01	5.24	1.04	5.34	1.05	5.65	1.08	5.85	1.10
	15.0	4.71	1.02	4.92	1.05	5.12	1.07	5.22	1.08	5.52	1.11	5.73	1.13
	18.0	4.59	1.06	4.79	1.08	5.00	1.10	5.10	1.11	5.40	1.15	5.60	1.17
	20.0	4.51	1.08	4.71	1.11	4.91	1.13	5.01	1.14	5.32	1.17	5.52	1.19
	22.0	4.43	1.11	4.63	1.13	4.83	1.15	4.93	1.16	5.24	1.20	5.44	1.22
	25.0	4.30	1.15	4.51	1.17	4.71	1.19	4.81	1.20	5.11	1.24	5.32	1.26
	28.0	4.18	1.19	4.38	1.21	4.59	1.23	4.69	1.25	4.99	1.28	5.19	1.30
	32.0	4.02	1.25	4.22	1.27	4.42	1.29	4.52	1.30	4.83	1.34	5.03	1.36
	35.0	3.89	1.30	4.10	1.32	4.30	1.34	**4.40**	**1.35**	4.70	1.38	4.91	1.41
	40.0	3.69	1.38	3.89	1.40	4.09	1.42	4.20	1.43	4.50	1.47	4.70	1.49
	43.0	3.57	1.43	3.77	1.45	3.97	1.48	4.07	1.49	4.35	1.50	4.50	1.50
	46.0	3.16	1.30	3.31	1.30	3.45	1.30	3.52	1.30	3.73	1.30	3.87	1.30

3D055838A

SYMBOLS

TC: Total capacity (kW)
PI: Power input (kW)

NOTES

1 Capacities are based on the following conditions.
Corresponding refrigerant piping length: 5m
Level difference: 0m
2 The bold line ▭ is indicated the standard condition.
3 The above is the value for connecting with the following indoor units.
2.0, 2.5, 3.5 kW Class; wall mounted C, D (GMS5) series.